

Customized Solar Panel Pv Ribbon Wire Energy Efficiency For Solar System

Basic Information

• Place of Origin: China

Brand Name: Golden Electric /OEM

• Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

IATF16949

Minimum Order Quantity:

• Packaging Details: Carton/Pallet


• Delivery Time: Peak Season Lead Time: more than 12

months Off Season Lead Time: within 15

workdays

• Payment Terms: LC, T/T, PayPal, Western Union

Supply Ability: 5000/Month



Product Specification

Substrate:

Materia: LeadCopper Content Of >=99.95%

• Transport Package: Roll

• Trademark: Golden Electric Or Customize

Origin: China
HS Code: 8537209000
Supply Ability: 5000/Month
After-sales Service: 3years
Warranty: 3years
Condition: New
Certification: ISO, CE


Application: IndustrialSpecification: All Kind Of Size, Different Sizes And

Specifications

Camaralana IIOA O O/Iva 4 IZa/Mila Ovalan I Danisa



More Images









Product Description

Product Description

PV Ribbon is engineered to individual client specifications with dimensional and physical property flexibility to fit your solar module design.

- *Rolled flat, from round wire for burr free ribbon with in-line gauge measurement for dimensional thickness and width accuracy & consistency;
- * This combination of processes results in supelrior coatings and a completely burr free product;
- * State of the art annealing ensures consistent physical properties with low yield strength, high elongation for low cell breakage;
- * Lead or Lead free consistent solders applied on all four sicdes post production for a perfect bond between solar cell and tabbing ribbon;
- * Precision levelled, wound and packaged for safe transport and problem-free strin

Main features:

- 1.Can be customized.
- 2.Stable quality.
- 3. Standard production chain and automatic line ensure fast delivery.
- 4. Passed SGS testing certification, fully in line with the European ROHS directive standards.

Product Parameters

1.0 ×0. 25 Datasheet	
Type Specification	1.0*0.25
Copper Content of Substrate	≥99.95%
Substrate Resistivity	≤0.01724Ω. mm2 /m
Fusion Point	143-189ºC
Single-sided Coating	20±5um
Thickness Tolerance	±0.01mm
Width Tolerance	±0.05mm
Elongation	≥25%
Tensile Strength	150~220MPa
RPO.2/Yield Strength RPO.2	≤65MPa
Sickle Bending	≤0.3%
Tabbing Ribbon Resistivity	≤0.0224Ω. mm2 /m
Solder ability(N)	≥1.ON

Details display









2021 NEW PRODUCTS 手工焊带 2021 NEW PRODUCTS <mark>圆丝光伏焊带</mark>

Connector pin, copper pin, Copper plug-in, copper pin, pin hard-

Hone



2021 NEW PRODUCTS 手工焊带

Committee and a committee of the committ





Packaging and Shipping





1) Are you a factory or trading company?

Yes we are factories.

2) What is your FOB port?

FOB Guangzhou, and we can according to customer requirements.

3) What is your delivery time?

3-7 days for samples, 10-30 days for large quantities, according to your order.

4) How about your after-sale service?

We can offer you timely and best after-sales service. Now we have built our relationship in many overseas countries like Brazil, Pakistan, Japan and German. It makes our after-sale service very easy and effective to reach you. Also our 24 hours online inquiry service is available.

5) Can I have my own logo on your products? Yes, OEM&ODM service is available.

Guangzhou Golden Electric Co., Ltd.

008618998498109

eva@china-golden.com.cn

chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city, Guangdong province, China