



## Industrial IP55 110V 32a Interlocked Socket White Blue for Power Supply

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month



### Product Specification

- Interface Type: AC/DC
- Nominal Voltage: 110V/220V/380V/415V
- Brand: Golden Electric /OEM
- Protection Degree: IP44/IP67/IP55
- Rated Voltage: 110V/220V/380V/415V
- Rated Current: 16A/32A
- Color: White Blue Yellow Red
- Earth Contact Position: 6h ,9h
- Product Name: Industrial Plug And Socket
- Material: IP66 Nylon
- Contact Material: Tinned Copper
- Transport Package: Standard Export Carton
- Specification: 2P+E 3P+E 3P+N+E
- Trademark: Golden Or Natural, Or Customer Brand
- Origin: China



### More Images



for more products please visit us on [chinagoldene.com](http://chinagoldene.com)

## Product Description

### Product Description

#### IP55 Waterproof 400v Industrial Plug And Socket

##### Function:

- 1, Our products have undergone the tests under the extreme conditions such as the pesky cold and hot, dustproof, immersed in water and so on, and they have got the certificates from relevant authorized organizations according to the international standard.
- 2, Certificates: **CCC, CE, China Classification Society,ISO9001,CQC**
- 3, German industrial standard DIN VDE6032,European/Inernational standard EN/IEC 60 309-2
- 4, Application: it is widely applied in the electrical Field, particularly in the steel, Chemical, electrical, absenteeism, ports, airports, oil exploration, foods, subway and other places.
- 5, Besides the **waterproof** and **dustproof** advantages, have **impact-resistance**, **anti-aging**,  
Never rusting features. Also have dustproof, **damp-proof**, **anticorrosion**, **flame-dustproof** and **anti-aging properties** as well as advantages such as **high temperature resistance**, large flexibility, **good impact resistance**, high degree of finish, soft contact of large current and so on.
- 6, Easy to installation , plug and socket are easy to put in and out at any time and easy to turn on or off the power.
- 7, Many combined modes so that can reach the customer's demands
- 8, The unique design and exquisite appearance can be used in any harsh environment

### Product Parameters



Information	
Product	Industrial Plug and Socket
Rated Voltage	110V/220V/380V/415V
Material	Nylon PA66
Color	White/Blue/Yellow/Red
Earth Contact Position	6h,9h
Features	Safe,Durable,Timesaving
External Screws	Acid-Proof S/S
Contact Material	Tinned Copper

#### Testing & Quality Ensure

Quality is our only faith,we have a professional Research and development team and high-quality workers sparing no efforts for pursuit of perfect production.We equip with a series of inspection devices for testing and ensuring every product we produce is perfect .

Both the quality and performance of our products can match the international standard EN/IEC60309-2 and the national standard GB 11919-2001 Products have obtained international certifications, such as CE,ROHS,TUV,CB,etc.


#### Our Advantage

We provide different series products for different environment.Using fresh material importing good quality copper and on parts to make sure product with longer mechanical life resistance to severeweather, ageing ,alkali resistance waterproof and dust prevention.

### Product Details




**E-114** (No.: YT18183)  
**E-124** (No.: YT18187)  
电流 Current(A):16A,32A  
电压 Voltage(V):380-415V~  
防护等级 Protection degree:IP67  
  
3P+E



Earth contact position Rated current(A)	6h	
	16	32
Pole	4	
Dimension(mm)	a	155
	b	101
Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6




**E-115** (No.: YT18184)  
**E-125** (No.: YT18188)  
电流 Current(A):16A,32A  
电压 Voltage(V):220-380V~  
240-415V~  
防护等级 Protection degree:IP67  
  
3P+N+E



Earth contact position Rated current(A)	6h	
	16	32
Pole	5	
Dimension(mm)	a	155
	b	106
Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6



**E-133** (No.: YT18189)  
**E-143** (No.: YT18192)  
电流 Current(A):63A,125A  
电压 Voltage(V):220-250V~  
防护等级 Protection degree:IP67  
  
2P+E



Earth contact position Rated current(A)	6h	
	63	125
Pole	3	
Dimension(mm)	a	171
	b	170
	c	250
	d	118
	e	137
	f	104
Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50




**E-134** (No.: YT18190)  
**E-144** (No.: YT18193)  
电流 Current(A):63A,125A  
电压 Voltage(V):380-415V~  
防护等级 Protection degree:IP67  
  
3P+E



Earth contact position Rated current(A)	6h	
	63	125
Pole	4	
Dimension(mm)	a	171
	b	170
	c	250
	d	118
	e	137
	f	104
Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50



**E-135** (No.: YT18191)  
**E-145** (No.: YT18194)  
电流 Current(A):63A,125A  
电压 Voltage(V):220-380V~  
240-415V~  
防护等级 Protection degree:IP67  
  
3P+N+E



Earth contact position Rated current(A)	6h	
	63	125
Pole	5	
Dimension(mm)	a	171
	b	170
	c	250
	d	118
	e	137
	f	104
Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50



**E-1013** (No.: YT18195)  
输入 Input:1 plug  
16A 220V  
输出 Output:3 sockets  
16A 220V  
防护等级 Protection degree:IP67  
  
2P+E



**E-1014** (No.: YT18196)  
输入 Input:1 plug  
16A 380V  
输出 Output:2 sockets  
16A 380V  
防护等级 Protection degree:IP67  
  
3P+E



	<p><b>E-035</b> (No.: YT18135) <b>E-045</b> (No.: YT18138) 电流 Current(A):63A,125A 电压 Voltage(V):220-380V~ 240-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+N+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>63 125</td></tr><tr><td>Pole</td><td>5</td></tr><tr><td>Dimension(mm)</td><td>a 240 295 b 115 126 c 30 44.5</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>6-16 16-50</td></tr></table>	Earth contact position	6h	Rated current(A)	63 125	Pole	5	Dimension(mm)	a 240 295 b 115 126 c 30 44.5	Cable nominal cross-section area (mm²)	6-16 16-50
Earth contact position	6h												
Rated current(A)	63 125												
Pole	5												
Dimension(mm)	a 240 295 b 115 126 c 30 44.5												
Cable nominal cross-section area (mm²)	6-16 16-50												
	<p><b>E-213-4</b> (No.: YT18139) <b>E-223-4</b> (No.: YT18143) 电流 Current(A):16A,32A 电压 Voltage(V):110-130V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>		<table><tr><td>Earth contact position</td><td>4h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>3</td></tr><tr><td>Dimension(mm)</td><td>a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	4h	Rated current(A)	16 32	Pole	3	Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	4h												
Rated current(A)	16 32												
Pole	3												
Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p><b>E-213</b> (No.: YT18140) <b>E-223</b> (No.: YT18144) 电流 Current(A):16A,32A 电压 Voltage(V):220-240V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>3</td></tr><tr><td>Dimension(mm)</td><td>a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	6h	Rated current(A)	16 32	Pole	3	Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	6h												
Rated current(A)	16 32												
Pole	3												
Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p><b>E-214</b> (No.: YT18141) <b>E-224</b> (No.: YT18145) 电流 Current(A):16A,32A 电压 Voltage(V):380-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>4</td></tr><tr><td>Dimension(mm)</td><td>a 153 175 b 87 97 c 6-15 10-20 d 80 93 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	6h	Rated current(A)	16 32	Pole	4	Dimension(mm)	a 153 175 b 87 97 c 6-15 10-20 d 80 93 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	6h												
Rated current(A)	16 32												
Pole	4												
Dimension(mm)	a 153 175 b 87 97 c 6-15 10-20 d 80 93 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p><b>E-215</b> (No.: YT18142) <b>E-225</b> (No.: YT18146) 电流 Current(A):16A,32A 电压 Voltage(V):220-380V~ 240-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+N+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>5</td></tr><tr><td>Dimension(mm)</td><td>a 155 185 b 93 104 c 8-16 12-22 d 87 100 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	6h	Rated current(A)	16 32	Pole	5	Dimension(mm)	a 155 185 b 93 104 c 8-16 12-22 d 87 100 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	6h												
Rated current(A)	16 32												
Pole	5												
Dimension(mm)	a 155 185 b 93 104 c 8-16 12-22 d 87 100 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p><b>E-233</b> (No.: YT18147) <b>E-243</b> (No.: YT18150) 电流 Current(A):63A,125A 电压 Voltage(V):220-250V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>63 125</td></tr><tr><td>Pole</td><td>3</td></tr><tr><td>Dimension(mm)</td><td>a 261 305 b 114 115 c 30 44.5 d 112 130</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>6-16 16-50</td></tr></table>	Earth contact position	6h	Rated current(A)	63 125	Pole	3	Dimension(mm)	a 261 305 b 114 115 c 30 44.5 d 112 130	Cable nominal cross-section area (mm²)	6-16 16-50
Earth contact position	6h												
Rated current(A)	63 125												
Pole	3												
Dimension(mm)	a 261 305 b 114 115 c 30 44.5 d 112 130												
Cable nominal cross-section area (mm²)	6-16 16-50												

	<b>E-013-4</b> (No.: YT18001) <b>E-023-4</b> (No.: YT18005) 电流 Current(A):16A,32A 电压 Voltage(V):110-130V~ 防护等级 Protection degree:IP44  2P+E		<table><tr><td>Earth contact position</td><td colspan="2">4h</td></tr><tr><td>Rated current(A)</td><td>16</td><td>32</td></tr><tr><td>Pole</td><td colspan="2">3</td></tr><tr><td>Dimension(mm)</td><td>a</td><td>122</td></tr><tr><td></td><td>b</td><td>57</td></tr><tr><td></td><td>c</td><td>50</td></tr><tr><td></td><td>φ</td><td>6</td></tr><tr><td>Cable nominal cross-section area (mm<sup>2</sup>)</td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position	4h		Rated current(A)	16	32	Pole	3		Dimension(mm)	a	122		b	57		c	50		φ	6	Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6
Earth contact position	4h																										
Rated current(A)	16	32																									
Pole	3																										
Dimension(mm)	a	122																									
	b	57																									
	c	50																									
	φ	6																									
Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6																									
	<b>E-013</b> (No.: YT18002) <b>E-023</b> (No.: YT18006) 电流 Current(A):16A,32A 电压 Voltage(V):220-240V~ 防护等级 Protection degree:IP44  2P+E		<table><tr><td>Earth contact position</td><td colspan="2">6h</td></tr><tr><td>Rated current(A)</td><td>16</td><td>32</td></tr><tr><td>Pole</td><td colspan="2">3</td></tr><tr><td>Dimension(mm)</td><td>a</td><td>122</td></tr><tr><td></td><td>b</td><td>57</td></tr><tr><td></td><td>c</td><td>50</td></tr><tr><td></td><td>φ</td><td>6</td></tr><tr><td>Cable nominal cross-section area (mm<sup>2</sup>)</td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position	6h		Rated current(A)	16	32	Pole	3		Dimension(mm)	a	122		b	57		c	50		φ	6	Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6
Earth contact position	6h																										
Rated current(A)	16	32																									
Pole	3																										
Dimension(mm)	a	122																									
	b	57																									
	c	50																									
	φ	6																									
Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6																									
	<b>E-014</b> (No.: YT18003) <b>E-024</b> (No.: YT18007) 电流 Current(A):16A,32A 电压 Voltage(V):380-415V~ 防护等级 Protection degree:IP44  3P+E		<table><tr><td>Earth contact position</td><td colspan="2">6h</td></tr><tr><td>Rated current(A)</td><td>16</td><td>32</td></tr><tr><td>Pole</td><td colspan="2">4</td></tr><tr><td>Dimension(mm)</td><td>a</td><td>122</td></tr><tr><td></td><td>b</td><td>57</td></tr><tr><td></td><td>c</td><td>50</td></tr><tr><td></td><td>φ</td><td>6</td></tr><tr><td>Cable nominal cross-section area (mm<sup>2</sup>)</td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position	6h		Rated current(A)	16	32	Pole	4		Dimension(mm)	a	122		b	57		c	50		φ	6	Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6
Earth contact position	6h																										
Rated current(A)	16	32																									
Pole	4																										
Dimension(mm)	a	122																									
	b	57																									
	c	50																									
	φ	6																									
Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6																									
	<b>E-015</b> (No.: YT18004) <b>E-025</b> (No.: YT18008) 电流 Current(A):16A,32A 电压 Voltage(V):220-380V~ 240-415V~ 防护等级 Protection degree:IP44  3P+N+E		<table><tr><td>Earth contact position</td><td colspan="2">6h</td></tr><tr><td>Rated current(A)</td><td>16</td><td>32</td></tr><tr><td>Pole</td><td colspan="2">5</td></tr><tr><td>Dimension(mm)</td><td>a</td><td>130</td></tr><tr><td></td><td>b</td><td>75</td></tr><tr><td></td><td>c</td><td>64</td></tr><tr><td></td><td>φ</td><td>8</td></tr><tr><td>Cable nominal cross-section area (mm<sup>2</sup>)</td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position	6h		Rated current(A)	16	32	Pole	5		Dimension(mm)	a	130		b	75		c	64		φ	8	Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6
Earth contact position	6h																										
Rated current(A)	16	32																									
Pole	5																										
Dimension(mm)	a	130																									
	b	75																									
	c	64																									
	φ	8																									
Cable nominal cross-section area (mm <sup>2</sup> )	1-2.5	2.5-6																									
	<b>E-033</b> (No.: YT18017) <b>E-043</b> (No.: YT18020) 电流 Current(A):16A,125A 电压 Voltage(V):220-240V~ 防护等级 Protection degree:IP67  2P+E		<table><tr><td>Earth contact position</td><td colspan="2">6h</td></tr><tr><td>Rated current(A)</td><td>63</td><td>125</td></tr><tr><td>Pole</td><td colspan="2">3</td></tr><tr><td>Dimension(mm)</td><td>a</td><td>231.5</td></tr><tr><td></td><td>b</td><td>110</td></tr><tr><td></td><td>c</td><td>16-38</td></tr><tr><td></td><td>φ</td><td>110</td></tr><tr><td>Cable nominal cross-section area (mm<sup>2</sup>)</td><td>6-16</td><td>16-50</td></tr></table>	Earth contact position	6h		Rated current(A)	63	125	Pole	3		Dimension(mm)	a	231.5		b	110		c	16-38		φ	110	Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50
Earth contact position	6h																										
Rated current(A)	63	125																									
Pole	3																										
Dimension(mm)	a	231.5																									
	b	110																									
	c	16-38																									
	φ	110																									
Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50																									
	<b>E-034</b> (No.: YT18018) <b>E-044</b> (No.: YT18021) 电流 Current(A):16A,125A 电压 Voltage(V):380-415V~ 防护等级 Protection degree:IP67  3P+E		<table><tr><td>Earth contact position</td><td colspan="2">6h</td></tr><tr><td>Rated current(A)</td><td>63</td><td>125</td></tr><tr><td>Pole</td><td colspan="2">4</td></tr><tr><td>Dimension(mm)</td><td>a</td><td>231.5</td></tr><tr><td></td><td>b</td><td>110</td></tr><tr><td></td><td>c</td><td>16-38</td></tr><tr><td></td><td>φ</td><td>110</td></tr><tr><td>Cable nominal cross-section area (mm<sup>2</sup>)</td><td>6-16</td><td>16-50</td></tr></table>	Earth contact position	6h		Rated current(A)	63	125	Pole	4		Dimension(mm)	a	231.5		b	110		c	16-38		φ	110	Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50
Earth contact position	6h																										
Rated current(A)	63	125																									
Pole	4																										
Dimension(mm)	a	231.5																									
	b	110																									
	c	16-38																									
	φ	110																									
Cable nominal cross-section area (mm <sup>2</sup> )	6-16	16-50																									







Company Profile



- Golden Electric Co.,Ltd ,was foundad in 2007, we are professional for make **AC and DC electric items** such as cable gland,MC4 Connector, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Indicator lamp,Solar Charge Controller,Industrial plug and socket,Busbar Insulator,Meter Socket,Wind Turbine, Terminal Block,Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

## FAQ

### 1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China- more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the world-class companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

### 2) Q:Your products?

A: Golden electric is factory for Automatic transfer swithc, Surge protector device, distribution box Enclosure, inverter, DC fuse etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001 ,SGS etc.

### 3) Q: Do you have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

### 4) Q: Your address ?

A: Locates in Guangzhou province, China,welcome to visit us

### 5) Q:What's the Industrial Plug and Socket guarantee?

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

### 6) Q:What's about MOQ? Delivery time ?

A: 1pcs for Industrial plug and socket.

### 7) Q: What's the payment term?

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

### 8) Q:What's your contact information ?

**Send us your **inquiry** !we will reply you in 24 hours !**

**If you need information about this product. Please **Click here** to contact me and we will provide you with more information about the products.**



**Guangzhou Golden Electric Co., Ltd.**



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city, Guangdong province, China