



IP44/IP67/IP55 Waterproof Coupler 3p E 4 Pins 16A 32A Industrial Plug and Socket Male Female Connector with Cover 220V 240V

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month



Product Specification

- Interface Type: AC/DC
- Nominal Voltage: 110V/220V/380V/415V
- Brand: Golden Electric /OEM
- Protection Degree: IP44/IP67/IP55
- Rated Voltage: 110V/220V/380V/415V
- Rated Current: 16A/32A
- Color: Blue Red
- Earth Contact Position: 6h ,9h
- Product Name: Industrial Plug And Socket
- Material: IP66 Nylon
- Contact Material: Tinned Copper
- Model: Male And Female Connector
- Transport Package: Standard Export Carton
- Specification: 2P+E 3P+E 3P+N+E
- Trademark: Golden Or Natural, Or Customer Brand



More Images



for more products please visit us on chinagoldene.com

Product Description

Product Description

IP44 Waterproof 400v Industrial Plug And Socket

Function:

- 1, Our products have undergone the tests under the extreme conditions such as the pesky cold and hot, dustproof, immersed in water and so on, and they have got the certificates from relevant authorized organizations according to the international standard.
- 2, Certificates: **CCC, CE, China Classification Society,ISO9001,CQC**
- 3, German industrial standard DIN VDE6032,European/International standard EN/IEC 60 309-2
- 4, Application: it is widely applied in the electrical Field, particularly in the steel, Chemical, electrical, absenteeism, ports, airports, oil exploration, foods, subway and other places.
- 5, Besides the **waterproof** and **dustproof** advantages, have **impact-resistance**, **anti-aging**,
Never rusting features. Also have dustproof, **damp-proof**, **anticorrosion**, **flame-dustproof** and **anti-aging properties** as well as advantages such as **high temperature resistance**, large flexibility, **good impact resistance**, high degree of finish, soft contact of large current and so on.
- 6, Easy to installation , plug and socket are easy to put in and out at any time and easy to turn on or off the power.
- 7, Many combined modes so that can reach the customer's demands
- 8, The unique design and exquisite appearance can be used in any harsh environment

Product Parameters



Poles	2P+E
Color	Blue
Current(A)	16A
Voltage(V)	220-250V
Protection Degree	IP44
Earth Contact Position	6H
Outer Material	PA66
Conductor	Tinned Copper
IEC/EN Rating	IEC/EN 60309-2

Testing & Quality Ensure

Quality is our only faith,we have a professional Research and development team and high-quality workers sparing no efforts for pursuit of perfect production.We equip with a series of inspection devices for testing and ensuring every product we produce is perfect .

Both the quality and performance of our products can match the international standard EN/IEC60309-2 and the national standard GB 11919-2001 Products have obtained international certifications, such as CE,ROHS,TUV,CB,etc.

Our Advantage

We provide different series products for different environment.Using fresh material importing good quality copper and on parts to make sure product with longer mechanical life resistance to severeweather, ageing ,alkali resistance waterproof and dust prevention.



3pol 4pol 5pol
4h 4h 4h



3pol 4pol 5pol
8h 9h 9h



3pol 4pol 5pol
0% 0% 0%






3pol 4pol 5pol
7h 7h 7h

3pol 4pol 5pol
10% 10% 10%



1pol	3pol	4pol	5pol
2h	2h	2h	2h

pol






	<p>E-035 (No.: YT18135) E-045 (No.: YT18138) 电流 Current(A):63A,125A 电压 Voltage(V):220-380V~ 240-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+N+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>63 125</td></tr><tr><td>Pole</td><td>5</td></tr><tr><td>Dimension(mm)</td><td>a 240 295 b 115 126 c 30 44.5</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>6-16 16-50</td></tr></table>	Earth contact position	6h	Rated current(A)	63 125	Pole	5	Dimension(mm)	a 240 295 b 115 126 c 30 44.5	Cable nominal cross-section area (mm²)	6-16 16-50
Earth contact position	6h												
Rated current(A)	63 125												
Pole	5												
Dimension(mm)	a 240 295 b 115 126 c 30 44.5												
Cable nominal cross-section area (mm²)	6-16 16-50												
	<p>E-213-4 (No.: YT18139) E-223-4 (No.: YT18143) 电流 Current(A):16A,32A 电压 Voltage(V):110-130V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>		<table><tr><td>Earth contact position</td><td>4h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>3</td></tr><tr><td>Dimension(mm)</td><td>a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	4h	Rated current(A)	16 32	Pole	3	Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	4h												
Rated current(A)	16 32												
Pole	3												
Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p>E-213 (No.: YT18140) E-223 (No.: YT18144) 电流 Current(A):16A,32A 电压 Voltage(V):220-240V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>3</td></tr><tr><td>Dimension(mm)</td><td>a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	6h	Rated current(A)	16 32	Pole	3	Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	6h												
Rated current(A)	16 32												
Pole	3												
Dimension(mm)	a 147 175 b 71 97 c 6-15 10-20 d 71 93 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p>E-214 (No.: YT18141) E-224 (No.: YT18145) 电流 Current(A):16A,32A 电压 Voltage(V):380-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>4</td></tr><tr><td>Dimension(mm)</td><td>a 153 175 b 87 97 c 6-15 10-20 d 80 93 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	6h	Rated current(A)	16 32	Pole	4	Dimension(mm)	a 153 175 b 87 97 c 6-15 10-20 d 80 93 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	6h												
Rated current(A)	16 32												
Pole	4												
Dimension(mm)	a 153 175 b 87 97 c 6-15 10-20 d 80 93 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p>E-215 (No.: YT18142) E-225 (No.: YT18146) 电流 Current(A):16A,32A 电压 Voltage(V):220-380V~ 240-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+N+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>16 32</td></tr><tr><td>Pole</td><td>5</td></tr><tr><td>Dimension(mm)</td><td>a 155 185 b 93 104 c 8-16 12-22 d 87 100 sw 38 50</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>1-2.5 2.5-6</td></tr></table>	Earth contact position	6h	Rated current(A)	16 32	Pole	5	Dimension(mm)	a 155 185 b 93 104 c 8-16 12-22 d 87 100 sw 38 50	Cable nominal cross-section area (mm²)	1-2.5 2.5-6
Earth contact position	6h												
Rated current(A)	16 32												
Pole	5												
Dimension(mm)	a 155 185 b 93 104 c 8-16 12-22 d 87 100 sw 38 50												
Cable nominal cross-section area (mm²)	1-2.5 2.5-6												
	<p>E-233 (No.: YT18147) E-243 (No.: YT18150) 电流 Current(A):63A,125A 电压 Voltage(V):220-250V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>		<table><tr><td>Earth contact position</td><td>6h</td></tr><tr><td>Rated current(A)</td><td>63 125</td></tr><tr><td>Pole</td><td>3</td></tr><tr><td>Dimension(mm)</td><td>a 261 305 b 114 115 c 30 44.5 d 112 130</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td>6-16 16-50</td></tr></table>	Earth contact position	6h	Rated current(A)	63 125	Pole	3	Dimension(mm)	a 261 305 b 114 115 c 30 44.5 d 112 130	Cable nominal cross-section area (mm²)	6-16 16-50
Earth contact position	6h												
Rated current(A)	63 125												
Pole	3												
Dimension(mm)	a 261 305 b 114 115 c 30 44.5 d 112 130												
Cable nominal cross-section area (mm²)	6-16 16-50												

	<p>E-013-4 (No.: YT18001) E-023-4 (No.: YT18005)</p> <p>电流 Current(A):16A,32A 电压 Voltage(V):110-130V~ 防护等级 Protection degree:IP44</p> <p> 2P+E</p>	 <table><tr><th colspan="2">Earth contact position</th><th colspan="2">4h</th></tr><tr><th colspan="2">Rated current(A)</th><th>16</th><th>32</th></tr><tr><th colspan="2">Pole</th><th colspan="2">3</th></tr><tr><td>Dimension(mm)</td><td>a</td><td>122</td><td>141</td></tr><tr><td></td><td>b</td><td>57</td><td>77</td></tr><tr><td></td><td>c</td><td>50</td><td>64</td></tr><tr><td></td><td>φ</td><td>6</td><td>8</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td></td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position		4h		Rated current(A)		16	32	Pole		3		Dimension(mm)	a	122	141		b	57	77		c	50	64		φ	6	8	Cable nominal cross-section area (mm²)		1-2.5	2.5-6
Earth contact position		4h																																
Rated current(A)		16	32																															
Pole		3																																
Dimension(mm)	a	122	141																															
	b	57	77																															
	c	50	64																															
	φ	6	8																															
Cable nominal cross-section area (mm²)		1-2.5	2.5-6																															
	<p>E-013 (No.: YT18002) E-023 (No.: YT18006)</p> <p>电流 Current(A):16A,32A 电压 Voltage(V):220-240V~ 防护等级 Protection degree:IP44</p> <p> 2P+E</p>	 <table><tr><th colspan="2">Earth contact position</th><th colspan="2">6h</th></tr><tr><th colspan="2">Rated current(A)</th><th>16</th><th>32</th></tr><tr><th colspan="2">Pole</th><th colspan="2">3</th></tr><tr><td>Dimension(mm)</td><td>a</td><td>122</td><td>141</td></tr><tr><td></td><td>b</td><td>57</td><td>77</td></tr><tr><td></td><td>c</td><td>50</td><td>64</td></tr><tr><td></td><td>φ</td><td>6</td><td>8</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td></td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position		6h		Rated current(A)		16	32	Pole		3		Dimension(mm)	a	122	141		b	57	77		c	50	64		φ	6	8	Cable nominal cross-section area (mm²)		1-2.5	2.5-6
Earth contact position		6h																																
Rated current(A)		16	32																															
Pole		3																																
Dimension(mm)	a	122	141																															
	b	57	77																															
	c	50	64																															
	φ	6	8																															
Cable nominal cross-section area (mm²)		1-2.5	2.5-6																															
	<p>E-014 (No.: YT18003) E-024 (No.: YT18007)</p> <p>电流 Current(A):16A,32A 电压 Voltage(V):380-415V~ 防护等级 Protection degree:IP44</p> <p> 3P+E</p>	 <table><tr><th colspan="2">Earth contact position</th><th colspan="2">6h</th></tr><tr><th colspan="2">Rated current(A)</th><th>16</th><th>32</th></tr><tr><th colspan="2">Pole</th><th colspan="2">4</th></tr><tr><td>Dimension(mm)</td><td>a</td><td>122</td><td>141</td></tr><tr><td></td><td>b</td><td>57</td><td>77</td></tr><tr><td></td><td>c</td><td>50</td><td>64</td></tr><tr><td></td><td>φ</td><td>6</td><td>8</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td></td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position		6h		Rated current(A)		16	32	Pole		4		Dimension(mm)	a	122	141		b	57	77		c	50	64		φ	6	8	Cable nominal cross-section area (mm²)		1-2.5	2.5-6
Earth contact position		6h																																
Rated current(A)		16	32																															
Pole		4																																
Dimension(mm)	a	122	141																															
	b	57	77																															
	c	50	64																															
	φ	6	8																															
Cable nominal cross-section area (mm²)		1-2.5	2.5-6																															
	<p>E-015 (No.: YT18004) E-025 (No.: YT18008)</p> <p>电流 Current(A):16A,32A 电压 Voltage(V):220-380V~ 240-415V~ 防护等级 Protection degree:IP44</p> <p> 3P+N+E</p>	 <table><tr><th colspan="2">Earth contact position</th><th colspan="2">6h</th></tr><tr><th colspan="2">Rated current(A)</th><th>16</th><th>32</th></tr><tr><th colspan="2">Pole</th><th colspan="2">5</th></tr><tr><td>Dimension(mm)</td><td>a</td><td>130</td><td>141</td></tr><tr><td></td><td>b</td><td>75</td><td>87</td></tr><tr><td></td><td>c</td><td>64</td><td>70</td></tr><tr><td></td><td>φ</td><td>8</td><td>8</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td></td><td>1-2.5</td><td>2.5-6</td></tr></table>	Earth contact position		6h		Rated current(A)		16	32	Pole		5		Dimension(mm)	a	130	141		b	75	87		c	64	70		φ	8	8	Cable nominal cross-section area (mm²)		1-2.5	2.5-6
Earth contact position		6h																																
Rated current(A)		16	32																															
Pole		5																																
Dimension(mm)	a	130	141																															
	b	75	87																															
	c	64	70																															
	φ	8	8																															
Cable nominal cross-section area (mm²)		1-2.5	2.5-6																															
	<p>E-033 (No.: YT18017) E-043 (No.: YT18020)</p> <p>电流 Current(A):16A,125A 电压 Voltage(V):220-240V~ 防护等级 Protection degree:IP67</p> <p> 2P+E</p>	 <table><tr><th colspan="2">Earth contact position</th><th colspan="2">6h</th></tr><tr><th colspan="2">Rated current(A)</th><th>63</th><th>125</th></tr><tr><th colspan="2">Pole</th><th colspan="2">3</th></tr><tr><td>Dimension(mm)</td><td>a</td><td>231.5</td><td>295</td></tr><tr><td></td><td>b</td><td>110</td><td>123</td></tr><tr><td></td><td>c</td><td>16-38</td><td>30-64</td></tr><tr><td></td><td>φ</td><td>110</td><td>123</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td></td><td>6-16</td><td>16-50</td></tr></table>	Earth contact position		6h		Rated current(A)		63	125	Pole		3		Dimension(mm)	a	231.5	295		b	110	123		c	16-38	30-64		φ	110	123	Cable nominal cross-section area (mm²)		6-16	16-50
Earth contact position		6h																																
Rated current(A)		63	125																															
Pole		3																																
Dimension(mm)	a	231.5	295																															
	b	110	123																															
	c	16-38	30-64																															
	φ	110	123																															
Cable nominal cross-section area (mm²)		6-16	16-50																															
	<p>E-034 (No.: YT18018) E-044 (No.: YT18021)</p> <p>电流 Current(A):16A,125A 电压 Voltage(V):380-415V~ 防护等级 Protection degree:IP67</p> <p> 3P+E</p>	 <table><tr><th colspan="2">Earth contact position</th><th colspan="2">6h</th></tr><tr><th colspan="2">Rated current(A)</th><th>63</th><th>125</th></tr><tr><th colspan="2">Pole</th><th colspan="2">4</th></tr><tr><td>Dimension(mm)</td><td>a</td><td>231.5</td><td>295</td></tr><tr><td></td><td>b</td><td>110</td><td>123</td></tr><tr><td></td><td>c</td><td>16-38</td><td>30-64</td></tr><tr><td></td><td>φ</td><td>110</td><td>123</td></tr><tr><td>Cable nominal cross-section area (mm²)</td><td></td><td>6-16</td><td>16-50</td></tr></table>	Earth contact position		6h		Rated current(A)		63	125	Pole		4		Dimension(mm)	a	231.5	295		b	110	123		c	16-38	30-64		φ	110	123	Cable nominal cross-section area (mm²)		6-16	16-50
Earth contact position		6h																																
Rated current(A)		63	125																															
Pole		4																																
Dimension(mm)	a	231.5	295																															
	b	110	123																															
	c	16-38	30-64																															
	φ	110	123																															
Cable nominal cross-section area (mm²)		6-16	16-50																															




E-614 (No.: YT18036)
E-624 (No.: YT18039)
电流 Current(A):16A,32A
电压 Voltage(V):380-415V~
防护等级 Protection degree:IP44

Earth contact position	6h	
	16	32
Rated current(A)	Pole 4	
Dimension(mm)	a	44
	b	23
	c	45
Cable nominal cross-section area (mm ²)	1-2.5	2.5-6




E-615 (No.: YT18037)
E-625 (No.: YT18040)
电流 Current(A):16A,32A
电压 Voltage(V):220-380V~
240-415V~
防护等级 Protection degree:IP44

Earth contact position	6h	
	16	32
Rated current(A)	Pole 5	
Dimension(mm)	a	44
	b	22
	c	55
Cable nominal cross-section area (mm ²)	1-2.5	2.5-6




E-633 (No.: YT18041)
E-643 (No.: YT18044)
电流 Current(A):63A,125A
电压 Voltage(V):220-240V~
防护等级 Protection degree:IP67

Earth contact position	6h	
	63	125
Rated current(A)	Pole 3	
Dimension(mm)	a	100
	b	80
	c	20
	d	109
	e	109
	f	6.5
Cable nominal cross-section area (mm ²)	6-16	16-50




E-634 (No.: YT18042)
E-644 (No.: YT18045)
电流 Current(A):63A,125A
电压 Voltage(V):380-415V~
防护等级 Protection degree:IP67

Earth contact position	6h	
	63	125
Rated current(A)	Pole 4	
Dimension(mm)	a	100
	b	80
	c	20
	d	109
	e	109
	f	6.5
Cable nominal cross-section area (mm ²)	6-16	16-50




E-635 (No.: YT18043)
E-645 (No.: YT18046)
电流 Current(A):63A,125A
电压 Voltage(V):220-380V~
240-415V~
防护等级 Protection degree:IP67

Earth contact position	6h	
	63	125
Rated current(A)	Pole 3	
Dimension(mm)	a	100
	b	80
	c	20
	d	109
	e	109
	f	6.5
Cable nominal cross-section area (mm ²)	6-16	16-50



E-113-4 (No.: YT18047)
E-123-4 (No.: YT18051)
电流 Current(A):16A,32A
电压 Voltage(V):110-130V~
防护等级 Protection degree:IP44

Earth contact position	4h	
	16	32
Rated current(A)	Pole 3	
Dimension(mm)	a	135
	b	92
	c	50
	d	3-18
Cable nominal cross-section area (mm ²)	1-1.25	2.5-6

A
06

Recommend Product





Company Profile



- Golden Electric Co.,Ltd ,was founded in 2007, we are professional for make **AC and DC electric items** such as cable gland,MC4 Connector, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Indicator lamp,Solar Charge Controller,Industrial plug and socket,Busbar Insulator,Meter Socket,Wind Turbine, Terminal Block,Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The products sell well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

FAQ

1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China- more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the world-class companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

2) Q:Your products?

A: Golden electric is factory for Automatic transfer switch, Surge protector device, distribution box Enclosure, inverter, DC fuse etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001 ,SGS etc.

3) Q: Do you have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

4) Q: Your address ?

A: Locates in Guangzhou province, China,welcome to visit us

5) Q:What's the Industrial Plug and Socket guarantee?

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

6) Q:What's about MOQ? Delivery time ?

A: 1pcs for Industrial plug and socket.

7) Q: What's the payment term?

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

8) Q:What's your contact information ?

Send us your **inquiry !we will reply you in 24 hours !**

If you need information about this product. Please **Click here to contact me and we will provide you with more information about the products.**



Guangzhou Golden Electric Co., Ltd.



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city, Guangdong province, China