

2p DC 600V 800V Surge Arrester Protector Solar Surge Protective Device for PV Solar System

Basic Information

• Place of Origin: China

Brand Name: Golden Electric /OEM

• Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

IATF16949

Minimum Order Quantity:

• Packaging Details: Carton/Pallet

Delivery Time: Peak Season Lead Time: more than 12

months Off Season Lead Time: within 15

workdays

• Payment Terms: LC, T/T, PayPal, Western Union

Supply Ability: 5000/Month



Product Specification

Model NO.: GD40-PV1000Shape: ModuleMaterial: Nylon

Brand: Golden Electric /OEM

• In: 20ka

• UC: 600/900/1000/1200/1500VDC

Imax: 40kaProtection Degree: IP20

• Used For: Solar PV System

• Color: Orange

Indication: Green(Good) Red(Replace)
 Transport Package: Standard Export Carton

Specification: 2P/3P

Trademark: Golden Or Netural, Or Customer Brand

• Origin: China



More Images









Product Description

Product Description

GD40-PV1000 series of DC Surge Protector Device (SPD) for use in Photovoltaic applications. Surge protective devices provide protection from lightning current and overvoltage surges in system from 500VDC to 1500VDC.

Provding power with photovoltaic solar panels is tremendously interesting in the context of renewable energy sources, as regards economical photovoltaic systems connected to the public electricity network. Because of their exposition, frequently in isolated sites and of the extended surface of photovoltaic system (PV), lightning strikes are a major components in risk to be assumed, both for the direct effect of lightning on the structures, and of the surge overvoltages on the installation. Cells are generally associated with inverters, has devolped a specfic Din Rail product to protect DC side of cells and inverters against surge in power plant or residential application.

With the MOV (Metal Oxside Varistor), the overvolatge will be limited at the value of the voltage protection level of the GD40-PV1000 DC surge protector, as recommended in standards and guides, insure all protections(between + and - , + and Ground, - and Ground). On each surge arrester, as option , an available auxiliary contact will inform the end life status to ensure a maximum effciency.

Product Features




Easy installation or retrofit Din-rail mountable Fail-safe / self-protected design Remote indicator (optional) with 3 pin NO/NC contact IP20 finger-safe design Visual indicator Small foot print


Product Parameters

Network configuration Photovoltaic (PV) Maximum continuous voltage(Uc) 600 /900 /1000 /1200 /1500VDC SPD to EN 61643-11 Type 2 SPD to IEC 61643-11 Class II Norminal discharge current (8/20μs) (In) 20kA Maximum discharge curent (8/20μs) (Imax) 40kA Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns Thermal Protection YES Operating State/ Fault Indication Green (good) / Red (Replace) Degree of protection IP 20 Insulating material / flammability class PA66, UL94 V-0 Protective Elements High Energy MOV Temperature range -40°C~+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) 35mm² (Solid) / 25mm² (Flexible) Remote Contacts (RC) Optional		
Maximum continuous voltage(Uc) 600 /900 /1000 /1200 /1500VDC SPD to EN 61643-11 Type 2 SPD to IEC 61643-11 Class II Norminal discharge current (8/20μs) (In) 20kA Maximum discharge current (8/20μs) (Imax) 40kA Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns	Technical Data / Type	GD40-PV1000
SPD to EN 61643-11 Type 2 SPD to IEC 61643-11 Class II Norminal discharge current (8/20μs) (In) 20kA Maximum discharge current (8/20μs) (Imax) 40kA Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns Thermal Protection YES Operating State/ Fault Indication Green (good) / Red (Replace) Degree of protection IP 20 Insulating material / flammability class PA66, UL94 V-0 Protective Elements High Energy MOV Temperature range -40°C~+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) 35mm² (Solid) / 25mm² (Flexible) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm		Photovoltaic (PV)
SPD to IEC 61643-11 Class II Norminal discharge current (8/20µs) (In) 20kA Maximum discharge curent (8/20µs) (Imax) 40kA Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns	Maximum continuous voltage(Uc)	600 /900 /1000 /1200 /1500VDC
Norminal discharge current (8/20μs) (In) 20kA Maximum discharge current (8/20μs) (Imax) 40kA Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns	SPD to EN 61643-11	Type 2
Maximum discharge curent (8/20μs) (Imax) 40kA Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns	SPD to IEC 61643-11	Class II
Voltage protection level (Up) ≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV Response time (Ta) < 25ns	Norminal discharge current (8/20µs) (In)	20kA
Response time (Ta) < 25ns Thermal Protection YES Operating State/ Fault Indication Green (good) / Red (Replace) Degree of protection IP 20 Insulating material / flammability class PA66, UL94 V-0 Protective Elements High Energy MOV Temperature range -40°C~+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) 35mm² (Solid) / 25mm² (Flexible) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Maximum discharge curent (8/20µs) (Imax)	40kA
Thermal Protection YES Operating State/ Fault Indication Green (good) / Red (Replace) Degree of protection IP 20 Insulating material / flammability class PA66, UL94 V-0 Protective Elements High Energy MOV Temperature range -40°C~+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) 35mm² (Solid) / 25mm² (Flexible) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Voltage protection level (Up)	≤ 2.5/ 3.0 /3.2 /3.6 /4.5kV
Operating State/ Fault IndicationGreen (good) / Red (Replace)Degree of protectionIP 20Insulating material / flammability classPA66, UL94 V-0Protective ElementsHigh Energy MOVTemperature range-40°C~+80°CAltitude13123 ft [4000m]Conductor Cross Section (max)35mm² (Solid) / 25mm² (Flexible)Remote Contacts (RC)OptionalFormatPluggableInternal configuration(Y) or (U)For mounting onDin Rail 35mm	Response time (Ta)	< 25ns
Degree of protection IP 20 Insulating material / flammability class Protective Elements Protective Elements High Energy MOV Temperature range -40°C~+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Thermal Protection	YES
Insulating material / flammability class PA66, UL94 V-0 Protective Elements High Energy MOV Temperature range -40°C~+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Operating State/ Fault Indication	Green (good) / Red (Replace)
Protective Elements High Energy MOV Temperature range -40°C∼+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) Remote Contacts (RC) Format Pluggable Internal configuration For mounting on High Energy MOV -40°C∼+80°C 13123 ft [4000m] 35mm² (Solid) / 25mm² (Flexible) Optional Pluggable (Y) or (U) For mounting on Din Rail 35mm	Degree of protection	IP 20
Temperature range -40°C∼+80°C Altitude 13123 ft [4000m] Conductor Cross Section (max) 35mm² (Solid) / 25mm² (Flexible) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Insulating material / flammability class	PA66, UL94 V-0
Altitude 13123 ft [4000m] Conductor Cross Section (max) 35mm² (Solid) / 25mm² (Flexible) Remote Contacts (RC) Optional Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Protective Elements	High Energy MOV
Conductor Cross Section (max) Remote Contacts (RC) Format Internal configuration For mounting on 35mm² (Solid) / 25mm² (Flexible) Optional Pluggable (Y) or (U) Din Rail 35mm	Temperature range	-40°C~+80°C
Remote Contacts (RC) Format Internal configuration For mounting on Optional Pluggable (Y) or (U) Din Rail 35mm	Altitude	13123 ft [4000m]
Format Pluggable Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Conductor Cross Section (max)	35mm² (Solid) / 25mm² (Flexible)
Internal configuration (Y) or (U) For mounting on Din Rail 35mm	Remote Contacts (RC)	Optional
For mounting on Din Rail 35mm	Format	Pluggable
1 1 3 1	Internal configuration	(Y) or (U)
Place of installation indoor installation	For mounting on	Din Rail 35mm
	Place of installation	indoor installation

Product Details

Dimensions







Application

Photovoltaic systems, AC/DC distribution, Power supplies, Industrial automation, Teleommunications, Motor Control Systems, PLC applications, Power transfer equipment, HVAC applications, UPS systems, Security systems, IT/Data centers, Medical equipment.

Packing







Recommand Product













Company Profile

- Golden Electric Co.,Ltd ,was founded in 2007, we are professional for make AC and DC electric items such as cable gland, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Wind Turbine, Solar product and so on.
- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.
- Golden is always striving hard to provide the best services and competitive price to all customers.

FAQ

1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China - more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the world-class companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

2) Q:Your products?

A: Golden electric is factory for Circuit Breaker, Automatic transfer switch, Surge protector device, distribution box Enclosure, inverter, DC fuse etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001, SGS etc.

3) Q: Do you have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

4) Q: Your address ?

A: Locates in Guangzhou province, China, welcome to visit us

5) Q:What's the Surge Protector Device(SPD) guarantee?

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

6) Q:What's about MOQ? Delivery time?

A: 1pcs for Surge Protector Device. Normally less than 100PCS with stock, quick support.

7) Q: What's the payment term?

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

8) Q:What's your contact information?

Send us your inquiry !we will reply you in 24 hours !



008618998498109

eva@china-golden.com.cn

chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city,Guangdong province,China