

20ka Imax Solar System Grade B Class SPD Plugable Structure Lightning Arrester Energy

ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15

LC, T/T, PayPal, Western Union

Basic Information

- Place of Origin:
- Brand Name: Golden Electric /OEM

China

IATF16949

workdays

5000/Month

1

- Certification:
- Minimum Order Quantity:
- Packaging Details: Carton/Pallet
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

 Shape: 	Module
 Material: 	Nylon
• Brand:	Golden Or OEM
• Voltage:	DC 500V, 550V, 800V, DC1000V(3p) 1200V, 1500V
• Us(Ka):	20ka
Imax(Ka):	40ka
• Series:	AC SPD, Surge Protector, Surge Protective Device
Color:	Orange
Altitude:	2000
Where To Use:	Solar PV System
Terminal Screwa:	M5
 Indication: 	Green(Good) Red(Replace)
 Class Test: 	II



More Images










Main Technical Parameters	型号 Model 参数 Technical Parameters	BV8-100	BV8-120
	最大持续工作电压 Maximum Continuous Operating Voltage Uc (V-) 385/420/440		0/440
	电压保护水平 Voltage Protection Level Up (V~) kV	≤2.5/3.0/3.2/3.5	
	标称放电电流 Nominal Discharge Current In (8/20 µ s)	60kA	80kA
	最大放电电流 Maximum Discharge Current Imax (8/20 µ s)	100kA	120kA
	响应时间 Response Time ns	<25	
	接入导线截面积 L/N The Cross Section of L/N Line6	16.25mm ²	
	接入接地线截面积PE The Cross Section of PE Line 25、35mm ⁴		mm²
	熔断器或断路器选型 Fuse or Switch(A)	63A	
	通讯。报警线载面积The Line Section of Communication and Alarm	≥1.5mm²	
	工作环境 Operating Environment ℃	-40°C~+85℃	
	相对湿度 Relative Humidity(25℃)	≤95%	
	安装 Installation	标准导轨道Standard Rail 35mm	
	外壳材料 Material of Outer Covering	玻璃纤维 Fiberglass	

防雷器采用35mm轨道型材安装,外形尺寸见图 The arrester is adopted 25mm of it

The arrester is adopted 35mm orbit material installation, see the chart for the outer shape size



Packaging & Shipping

Dimension

Surge Protective Device Arrester Packing List:

	Name	Specification	Packing quantity	GW/ctn	Carton size
	GDPS-4 DC	2P/20~40KA/DC500V	60	18.5	42*32*16.5cm
	GDPS-4 DC	2P/20~40KA/DC800V	60	18.5	42*32*16.5cm
	GDPS-4 DC	2P/20~40KA/DC1000V	60	19	42*32*16.5cm
	GDPS-4 DC	3P/20~40KA/DC100V	40	18.3	42*32*16.5cm
	GDPS-4 DC	2P/20~40KA/DC1200V	40	19.3	42*32*16.5cm

Packaging Details:

Customized Packing: Header card packing, Blister with card packing, Double blister packing, Canister packing, other


packing can be supplied according customers request.

Shipping:

- 1. By Air or by Sea for batch goods, Airport/ Port receiving;
- 2. Customers specifying freight forwarders or negotiable shipping methods!

Delivery Detail:

Shipped in 7 days after payment



- Golden Electric Co.,Ltd ,was foundad in 2017, we are professional for make AC and DC electric items such as cable gland, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.



Inverter:On grid and off grid inverter for 5 years warranty.

Surge protector: B,C,D Class, AC, DC type you can choose. Different types and discharge current you choose. Manual transfer switch: 1A~1600A, 3P/4P.

Combiner box :Metal and plastic,can design as you need.

Insulator:SM and EL series insulator

Metal Enclosure for Transfer switch: Metal box, size can color can be customized.

Plstic distribution box: Different ways, competitive price, welcome to contact.

Our Advantages

- 1.Best ensure 100% customer satisfaction.
- 2.Our products have one year guarantee.
- 3.Sample in design and easy to operate and maintain.
- 4.All electrical parts of products are made up for qualitified marterials.
- 5.No MOQ limited for the trial order.
- 6.We adopt good credit quality electrial appliances.
- 7.Best customer care and effcient after-sale services.
- 8.Don't hesitate to inquire us, we will reply you within 12 hours.



FAQ

Q1: If I'm interested in your Solar SPD when I can receive your quotation and detail information after send the enquiry?

A:All your enquiry will be replied in 8hours.

Q2:Your Solar SPD seems perfect but what's the difference between you and other suppliers?Because I find some cheaper price from others!

A: Our DC SPD is special for Solar system all the parts in the SPD are high quality customized.Not all the DC SPD are Solar SPD!

Q3:Can I get a sample before the order because I really don't how is your DC SPD quality?

A:Of course!We also think sample order is the best way to build the trust.

Q4:How's the delivery?Because I really need them is urgently?

A:For sample order 3~7days will be no problem.And for regular order we promise in 15days.

Q5:How's the warranty period for your DC SPD?

A:We offer one year warranty for our customer.

How to contact us

Send your Inquiry Details in the Below, please Click "**send**" Now! Good price and sample are waiting for you.

