

Black PVC Jacket BVV Electrical Cable Wire 2core 3 Core 4core 5 Core X1.5sqmm 2.5sqmm to 6sqmm

Basic Information

• Place of Origin: China

Brand Name: Golden Electric /OEM

• Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

IATF16949

Minimum Order Quantity:

Packaging Details: Carton/Pallet

• Delivery Time: Peak Season Lead Time: more than 12

months Off Season Lead Time: within 15

workdays

• Payment Terms: LC, T/T, PayPal, Western Union

• Supply Ability: 5000/Month



Product Specification

Material Shape: Round Wire
Range Of Application: Round Wire
Brand: Industrial
Voltage: 450/750V

• Conductor: Tinner Copper; CCC; CCA; Pure Copper

Core Color: BlackRated Temperature: 70, 90, 105

• Length: 100m/100y/or As Require

• Number Of Cores: Single Core- Multicores Power Cable

Sheath: Flexible PVC

Characteristics: Light Weight, High Conductivity

Size: Customized Size
Delivery: 7-12days
Sample Time: 3-5days
Current: AC Cable



More Images









Product Description



Terms:

- 1.OEM is welcomed
- 2.ISO/CE/ETL/ROHS/UL/SONCAP and other certifications are available
- 3. Competitive price and high quality offered.
- 4. Best service for you!

Basic Info:

- 1. Name: : Electric Wire/ Electric Cable/Power Cable/Single Cable/ Flat Cable/ Flexible Cable
- 2. Structure: Conduct---pure copper/copper clad copper/copper clad aluminum Insulation---blue/yellow/pink/grey/others you like
- 3. Size:According to Standard/Sample/Customer's request.
- 4. The material of the inner conductor and outer sheath materials in accordance with customer requirements.

ELECTRIC WIRE:

- 1.OEM is welcomed
- 2.ISO/ETL/ROHS/CE/UL/SONCAP and other certifications are available
- 3.Competitive price and high quality.
- 4. Best service!

Product Description:

Intruduction of the Electric Wire PVC Insulated Single Core H05V-U / H07V-U/ H07V-R wire:

- 1, The national certification of qualified manufacturers
- 2, Standard: GB 5023.1, IEC 60227/228, VDE
- 3, CE, RoHS, ISO, SGS Certificate
- 4, Meet European standards and can be customized according to customer requirements
- 5, OEM, ODM cooperation

PVC insulation flexible wire

Applications:

harmonized PVC European single-conductor hook-up wires with a solid bare copper core. Ideal for the internal wiring of appliances, apparatus, switchboards and distributor boards or where a solid core is required. Suitable in dry rooms for fixed and flexible laying. May be used for exposed and embedded conduits. Found in electronic and electrical equipment and switchgear cabinets designed for export to a European country for MRO replacement of European made equipment wire. The products is suitable for use in power installations, fixed wiring or flexible connections for electrical appliances, Like lighting, electronic equipment, instrument and communication equipment with rated voltage 300/500V, 450/750V, The Operating temperature: Allowing the wire of work for long time should not exceed +70 centigrade.

SPECIFICATIONS:

Nominal area of conductor	No./Dia. Of Conductor	Max.O.D	Approx.Weig
mm2	mm	mm2	kg/km
1x0.75	1x1/0.97	4.3	23
1x1.0	1x1/1.13	4.5	26.4
1x1.5(A)	1x1/1.38	4.9	34.6
1x1.5(B)	1x7/0.52	5.2	36.5
1X2.5(A)	1x1/0.85	5.8	46.4
1X4(A)	1x1/2.25	6.4	65.9
1X4(B)	1x7/0.85	6.8	73.7
1X6(A)	1x1/2.76	7.0	91.6
1X10	1x7/1.35	8.8	152.0
2X1.5(A)	2x1/1.38	10.0	109
2X1.5(B)	2x7/0.52	10.5	123
2X2.5(A)	2x1/1.78	11.5	157
2X2.5(B)	2x7/0.68	12.0	172
2X4(A)	2x1/2.25	12.5	205
2X4(B)	2x7/0.85	13.0	222
2X6(A)	2x1/2.76	13.5	265
2X6(B)	2x7/1.04	14.0	286
2X10	2x7/1.35	17.5	471
3X1.5(A)	3x1/1.38	10.5	136
3X1.5(B)	3x7/0.52	11.0	146
3X2.5(A)	3x1/1.78	12.0	190
3x2.5(B)	3X7/0.68	12.5	207
3X4(A)	3X1/2.25	13.0	252

3X4(B)	3X7/0.85	13.5	272
3X6(A)	3X1/2.76	14.5	344
3X10	3X7/1.35	19.0	574
4X1.5(A)	4X1/1.38	11.5	164
4X1.5(B)	4X7/0.52	12.0	174
4X2.5(B)	4X7/0.68	13.5	252
4X4(A)	4X1/2.25	14.5	321
4X4(B)	4X7/0.85	15.0	346
4X6(A)	4X1/1.04	16.0	470
4X6(B)	4X7/2.76	17.0	439
5X1.5(A)	5X1/1.38	12.0	192
5X1.5(B)	5X7/0.52	12.5	205
5X2.5(A)	5X1/1.78	14.0	272
5X2.5(B)	5X7/0.68	14.5	292
5X4(A)	5X1/2.25	16.0	397
5X4(B)	5X7/0.85	17.0	418
5X6(A)	5X1/2.76	17.5	518
5X6(B)	5X7/1.04	18.5	550

PRINTING WAYS



Application







Security & Protection System



intelligent safe-guard system







fire fighting system



Industrial construction

MAIN PRODUCTS



Packaging & Shipping

Packaging & Shipping

Packing: Steel wooden drum (fumigation) Cable length in each drum: 1000m/2000m or as per actual cable length requirements. Drum size: As per cable length and container size *In order to quote you accurate price, kindly tell us your needed

cable length quantity. Larger quantity, more discount benefit ready for you! Shipping Port:Tianjin, Qingdao, or other ports as per

your requireents. Sea freight:FOB/C&F/CIF quotation are all available. *For some countries such as Africa countries, middle east

countries, our sea freight quotation is much cheaper than clients get from local shipping agency.



Company Profile

- Golden Electric Co.,Ltd ,was founded in 2017, we are professional for make AC and DC electric items such as isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product and so on.
- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.
- Golden is always striving hard to provide the best services and competitive price to all customers.







Related Products



FAQ

Q:How and how long can I get a sample to check your quality?

A: After price confirmation, you can require for samples to check our quality. Then after you send us confirmed files, the samples will be ready for delivery in 7 days. The samples will be sent to you via express and arrive in 5-7 workdays.

Q:How to order our product?

- A: 1). Please tell us the model and quantity and other request you need.
- 2). We make the PI for you.
- 3). After you confirm the PI, we arrange the order for you after receiving your payment.
- 4). After the goods finished, we send the goods out to you and tell you the tracking number.
- 5). We will track your goods until you receive the goods.

Q: Can I have a visit to your factory before the order?

A: Welcome! Our factory address: Dongan Industrial Zone, Yueqing City, Wenzhou, Zhejiang, China (Mainland)

Q: What's your shipment method?

A: We ship by Express, by air, by sea, by train. Normally we checked and compare, then provide customer the most proper shipment method.

Q: What's about MOQ?

A: First order MOQ=1pcs

Q: If i want to release order, what's the payment method you accept?

A: We accept T/T, Paypal, Western union, etc.

Q: If i want to release order, what's the process?

A: Thanks. You can send inquiry to us by alibaba, or send us by email, we will reply within 24hrs.

Our committent

BETTER PRICE than other sellers for you because of Factory Direct Sale.
BETTER QUALITY than before caused by our 10+ years trading experience.

STOCK IN TRADE always own to our Fast & Professional production line. $\label{lem:fast-delivery} \textbf{FAST-DELIVERY-always-made-by-our-GROUP's-Enthusiam}.$ TIMING REPLY in 24 hours all about our TEAM's Passion & Patience. Send your Inquiry Details in the Below, Click "Send" Now~ YOUR BENEFITS IS OUR BUSINESS!!!



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city,Guangdong province,China