

Environmental Protection GSTP-25 500V DC Cylindrical 10X38 Solar PV Fuse Link at Best

Basic Information

Place of Origin: China

Brand Name: Golden Electric /OEM

• Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

IATF16949

Minimum Order Quantity:

• Packaging Details: Carton/Pallet

Delivery Time: Peak Season Lead Time: more than 12

months Off Season Lead Time: within 15

workdays

• Payment Terms: LC, T/T, PayPal, Western Union

Supply Ability: 5000/Month



Product Specification

Execution Standard: National Standard

Brand: Golden Or Netural Or Customer Brand

Model No.: Gstp-25

• Standard: High Quality CE&TUV Certificate

• Current: 1A,2A,3A,4A,5A,6A,8A,10A,12A,15A,20A,25/

Voltage: 1000VDC
Giggest Block Ability(Ka: 33ka
Working Temperature: "-5°"to +40°
Installation Altitude: ≤2000m
Protection Degree: IP20
Dimension: 10X38

Name: Ceramic Solar DC Fuse PV-30 10A Fuse
 Transport Package: Standard Export Box Package Carton Size

420/240/33

Specification: Different Sizes And Specifications



More Images









Product Description

Product Description


Fuse is consisted of fuse-link and fuse-base. The fuse-link is made up of fuse-element with variable cross-section or just a wire, either of which is enclosed in a fuse-tube of high strength ceramics. The fuse-tube is filled with special quartz sands in a particular density, acting as an arc-extinguish media. The fuse is of high breaking capacity, perfect current cutting-off characteristic and low power dissipation.

Fuse filament Pure T2 Copper Element-Double Copper Cap Siver Coating-High Strength Porcelain Body-High Purity Quartz Sands



Product Parameters


| 序号 No. | 产品型号 Product model | 国内外同类产品 Domestic and oversea similar products | 额定 电压 Rated Voltage | 额定 电流 Rated current (A) | 外形尺寸 Overall dimension (mm) | |
|-----------|-----------------------|---|---------------------------|----------------------------------|-----------------------------------|--|
| 18043 | RO06 | RO06 | (V) 250/380 | 1~32 | ΦD×L Φ12.7×29 | |
| | 100000 | 227.7.7 | 77.71.71.71 | | | |
| 18044 | RO07 | RO07 | 600 | 10~100 | Ф30×57 | |
| 18045 | RO14 | RT19-16 gF1 | 500 | 0.5~20 | Ф8.5×31.5 | |
| 18046 | RO14A | RT19-16 gF1 | 250 | 0.5~20 | Ф8.5×23 | |
| 18047 | RO15 | RT14-20 gF2 RT18-32 RT19-25 | 380/500 | 0.5~32 | Ф10.3×38 | |
| 18048 | RO15A | | 250 | 0.5~16 | Ф10.3×25.8 | |
| 18049 | RO15B | | 250/500 | 0.5~25 | Ф10.3×31.5 | |
| 18050 | RO15C | | 380/500 | 0.5~32 | Φ10.3×35 | |
| 18051 | RO15T | ATQR KTK | 380/600 | 0.5~32 | Ф10.3×38 | |
| 18052 | RO16 | RT14-32 gF3 RT18-63 RT19-40 | 380/660 | 2~50 | Ф14.3×51 | |
| 18053 | RO17 | RT14-63 gF4 RT18-125 RT19-100 | 380/660 | 10~125 | Ф22.2×58 | |
| 18054 | RO19 | FRS TRS FLSR | 600 | 0.5~32 | Ф20.5×127 | |
| 18055 | RO19H | FRS-R | 600 | 0.5~63 | Ф20.5×127 | |
| 18056 | RO54 | | 250 | 0.5~16 | Φ5×20 | |
| 18057 | RO55 | | 250 | 0.5~16 | Ф5×25 | |
| 18058 | RO57 | | 250 | 0.5~16 | Ф6.3×25 | |
| 18059 | RO58 | | 250/500 | 0.5~16 | Φ6.3×31.5 | |




Product Types Choosing&Technical Parameters

| Washington Company | Rated Current | I²t (A²s) | | Power loss | Ordering | The net | Min |
|--------------------|------------------|-----------|----------|---------------|---------------|---------|-----------|
| Product Type | | Melting | Clearing | (w) 1.0 In | Code | weight | Package |
| SFPV-25 | 2A | 1.5 | 3.45 | 1.0 | SFPV-25A02 | | 10 pieces |
| SFPV-25 | 3A | 4.5 | 12 | 1.3 | SFPV-25A03 | | |
| SFPV-25 | 4A | 9.6 | 27 | 1.5 | SFPV-25A04 | | |
| SFPV-25 | 5A | 21 | 53 | 1.6 | SFPV-25A05 | | |
| SFPV-25 | 6A | 27 | 94 | 1.8 | SFPV-25A06 | 9.5g | |
| SFPV-25 | 8A | 35 | 105 | 2.1 | SFPV-25A08 | | |
| SFPV-25 | 10A | 41 | 122 | 2.3 | SFPV-25A10 | | |
| SFPV-25 | 12A | 57 | 148 | 2.7 | SFPV-25A12 | | |
| SFPV-25 | 15A(16A) | 34 | 206 | 2.9 | SFPV-25A15/16 | | |
| SFPV-25 | 20A | 47 | 310 | 3.6 | SFPV-25A20 | | |
| SFPV-25B | 20A | 1 | | 1 | SFPV-25B | 62g | |
| SFPV-25BX | 20A | 1 | | 1 | SFPV-25BX | 63.5g | 12 piece |

Product model meaning




Product Dimensions (mm) and Characteristics



- 1. **Shell:** PBT environmentally friendly plastic, 100% raw material pressed, with excellent electrical properties and heat aging resistance, flame retardant grade V-0:
- 2. **Terminal block:** Silver plated with copper, low temperature rise and low power consumption;
- 3. **Ultrasonic welding:** The appearance quality is good, firm and resistant to falling;
- 4. **Neutral salt spray test (NSS):** The whole product is more than 24h, able to withstand the harsh outdoor environment.
- 1. Silver plated cover: Good electrical conductivity;
- 2. **95% alumina melt pipe:** Excellent insulation performance and high mechanical strength;
- 3. Pure silver melt: Disconnect the fault circuit in time to ensure equipment safety;
- 4. Special curing process: Reduce temperature rise, improve the effectiveness of breaking, and reduce the risk of short circuit.

預期故障电流(安培) Prospective Current in Amps

Fuse temperature correction factor



Other Hot-Selling Products



Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2007, we are professional for make AC and DC electric items such as cable gland, isolator switch , fuse and fuse holder, Circuit breaker , distribution box , PV combiner box ,surge protector, Timer Switch,Industrial plug and socket,Wind Turbine, Solar product, busbar clamp and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.
- Golden is always striving hard to provide the best services and competitive price to all customers.

FAQ

1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China - more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the worldclass companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

2) Q:Your products?

A: Golden electric is factory for Circuit Breaker, Automatic transfer switch, Surge protector device, distribution box Enclosure, inverter, DC fuse, busbar clamp etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001, SGS etc.

3) Q: Do vou have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

4) Q: Your address?

A: Locates in Guangzhou province, China, welcome to visit us

5) Q:What's the Fuse, Fuse holder guarantee?

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

6) Q:What's about MOQ? Delivery time?

A: 1pcs for Fuse holder.

7) Q: What's the payment term?

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

8) Q:What's your contact information?

Send us your inquiry !we will reply you in 24 hours !





008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city, Guangdong province, China