

Sak Jxb 4mm2 Panel Mount Terminal Block Distribution Copper Material Connector for PA66 Nylon

Basic Information

Place of Origin: China

• Brand Name: Golden Electric /OEM

• Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

IATF16949

Minimum Order Quantity:

Packaging Details: Carton/Pallet

Delivery Time: Peak Season Lead Time: more than 12

months Off Season Lead Time: within 15

workdays

• Payment Terms: LC, T/T, PayPal, Western Union

Supply Ability: 5000/Month



Product Specification

Production Process: Injection Molding

• Interface Type: AC/DC

Brand: Golden Electric /OEMWiring Diameter: 22-12AWG/ 0.5-4mm2

• Screw Size: M3

Rated Voltage: 600V/800VRated Current: 3A/32A

Product Name: DIN Rail Screw Terminal Blocks

Material: PA66 Nylon

• Usage: Conduct Electricity, Transmission Of

Electrical Si

Connection Method: Screw ConnectionInstallation: DIN Rail Mounted

• Stripping Length: 12mm

• Transport Package: Standara Export Carton



More Images









Product Description

Product Description

SAK Series Terminals Block

The terminal block is a kind of accessory product used to realize electrical connection, which is industrially divided into the category of connectors. The terminal is used to facilitate the connection of the wire. It is actually a piece of metal sealed in insulating plastic. There are holes at both ends to insert the wire. There are screws for fastening or loosening. For example, two wires, sometimes Need to connect, sometimes need to disconnect, then you can use the terminal to connect them, and can be disconnected at any time, without having to weld them or entangled together, it is very convenient and fast.

Characteristics:


- 1. Reasonable installation design, strong versatility, SAK type can be installed.
- 2.Small size, full specification, JXB series high current terminals use reinforced accessories to install steel wire crimping frame and breakout board technology to ensure reliable contact.3.Bckets in beige and grey, the connecting-ground pedestal uses yellow and green color with more modern sense.

Product Parameters

Model	SAK-4EN			
Standard	UL	IEC		
Rated Volatge	600V	800V		
Rated Current	3A	32A		
Wiring Diameter	22-12AWG	0.5-4mm²		
Thickness/Width/End plate thickness	6.5/42/1.5mm			
Height(NS35: 7.5/ NS35: 15/ NS32)	47.5/55/47.5mm			
Rated impulse voltage, pollution degree	8kV/3			
Stripping length	12mm			
Screw size/torque	M3/0.5-1.	0Nm		
Insulation material/flame retardant grade	PA/V-	0		
Conductive Material	Copper			
Warranty	2years			
All Models of this series	SAK 2.5EN, SAK4EN, SAK6EN, SAK10EN, SAK16EN, SAK25EN, SAK35EN, SAK70EN, SAK-RD, SAK WTL6/1, SAK DK4Q			

All Models of SAK series	Current	Voltage	Wire Range (mm2)	Dimension(mm)
SAK 2.5EN/JXB2.5/35	24A	800V	2.5	40.1*6*41.1
SAK 4EN/JXB4/35	32A	800V	4	40.2*6.5*46
SAK 6EN/JXB6/35	41A	800V	6	40.2*7.9*46
SAK 10EN/JXB10/35	57A	800V	10	40.2*10.1*46
SAK 16EN/JXB16/35	76A	800V	16	50.2*12.2*51.7
SAK 25EN/JXB25/35	110A	800V	25	50.2*14.3*50.7
SAK 35EN/JXB35/35	125A	800V	35	58.25*18.1*61.88
SAK 70EN/JXB70/35	192A	800V	70	74.9*22*77.2
SAK-RD/JXB-RD	6.3A	800V	2.5	58.3*8.1*42
SAK WTL6/1/JXB WTL6/1	41A	800V	6	66.6*8.1*51.8
SAK DK4Q/JXB DK4Q	32A	800V	2.5	55.3*6.4*55.6

Product Details









	ype 厚度thickness:6	28 M Szuniversal ty	pe 厚度thickness:6.5	適用型universal ty	pe 厚度thickness:8
SAK 2.5EN		SAK 4 EN		SAK 6 EN	
0.2-2	.5mm2	0.2-4mm2		0.2-6mm2	
电流current24A	电压voltage: 800V	电流current:32A	电压voltage: 800V	电流current41A	电压voltage: 800V
2.5EN Q2位,3位,10位	(2.5Q 2-10)	4EN Q2位,3位,10位	(4ENQ 2-10)	6EN Q2位,3位,10位	(6ENQ 2-10)
EW35		EW35		EW35	
连续印字	(DEK5(110)	连续印字	(DEK5(110)	连续印字	(DEK5(110)
是 是 是 是 是 是 是 是 是 是 是 是 是 是 是 是 是 是 是	42 #Rithickness:10	题用型universal ty	12 pp 形度thickness:12	是 通用型universal ty	42 pp Mitchickness:14.5
SAK	10EN	SAK	16EN	SAK	25EN
0.2-1	0mm2	0.5-1	3mm2	0.5-1	6mm2
电流current 57A	电压voltage: 800V	电流current:76A	电压voltage: 800V	电流current 100A	电压voltage: 800V
10EN Q2位,3位,10位	(10ENQ 2-10)	16EN Q2位,3位,10位	(16ENQ 2-10)	16EN Q2位,3位,10位	(16ENQ 2-10)
E\	N35	EW35		EW35	
连续印字	(DEK5(110)	连续印字	(DEK5(110)	连续印字	(DEK5(110)
-					4
300100000000000000000000000000000000000	50 Allahickness:18		pe 厚原thickness:22	保險越歷 fuse typ	58 用限thickness.6 KR
SAK		SAK70	MICONIA (SA	S. Marie Mar
SAK 10-3	35EN	SAK70)/35EN)mm2	SA	KR 4mm2
SAK 10-3	35EN 5mm2	SAK70 25-70)/35EN)mm2	SA 0.2-4	KR 4mm2
SAK 10-3 电流current 125A 35EN 2位,3位,10位	35EN 5mm2 电压voltage: 800V	SAK7(25-7(电流current 192A 70Q 2位,3位	I/35EN Imm2 电压voltage: 800V	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V
SAK 10-3 电流current125A 35EN 2位,3位,10位	35EN 5mm2 电压voltage: 800V (35ENQ 2-10)	SAK7(25-7(电流current 192A 70Q 2位,3位	0/35EN 0mm2 电压voltage: 800V (70Q 2位,3位)	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)
BAK 10-3 电流current:125A 35EN 2位,3位,10位 EV 连续印字	35EN 5mm2 电压voltage: 800V (35ENQ 2-10)	SAK7(25-7(电流current 192A 70Q 2位,3位 EV	//35EN mm2 电压voltage: 800V (70Q 2位,3位)	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)
BAK 10-3 电流current 125A 35EN 2位,3位,10位 EV 连续印字	55EN 5mm2 电压voltage: 800V (35ENQ 2-10) W35 (DEK5(110)	SAK70 25-70 电流current 192A 70Q 2位,3位 EV 连续印字	735EN 2mm2 电压voltage: 800V (70Q 2位,3位) 735 (DEK5(110)	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)
BAK 10-3 电流current 125A 35EN 2位,3位,10位 EV 连续印字	#Exoltage: 800V (35ENQ 2-10) W35 (DEK5(110)	SAK70 25-70 电流current 192A 70Q 2位,3位 EV 连续印字	735EN 2mm2 电压voltage: 800V (70Q 2位,3位) /35 (DEK5(110)	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)
BAK 10-3 电流current.125A 35EN 2位,3位,10位 EV 连续印字	35EN 5mm2 电压voltage: 800V (35ENQ 2-10) W35 (DEK5(110)	SAK70 25-70 电流current192A 70Q 2位,3位 EV 连续印字	//35EN //mm2 电压voltage: 800V //70Q 2位,3位) //35 (DEK5(110)	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)
BAK 10-3 电流current:125A 35EN 2位,3位,10位 EV 连续印字 R	### #################################	SAK70 25-70 电流current192A 70Q 2位,3位 EV 连续印字 SAK 0.2-4 电流current41A WTK2-10位 2位,3位,4位,10位	MMM2 电压voltage: 800V (70Q 2位,3位) (35 (DEK5(110) WTK mm2 电压voltage: 400V (WTKQ2-10位)	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)
BAK 10-3 电流current.125A 35EN 2位,3位,10位 EV 连续印字 W用型double level DK・ 0.2-4 电流current.32A DK4Q Q2位,3位,10位	#Exoltage: 800V (35ENQ 2-10) W35 (DEK5(110) ### #################################	SAK70 25-70 电流current192A 70Q 2位,3位 EV 连续印字 SAK 0.2-4 电流current41A WTK2-10位 2位,3位,4位,10位	#無数 (DEK5(110) # 表	0.2-4 电流current6.3A 10EN Q2位,3位,10位	KR 4mm2 电压voltage: 500V (10Q 2-10)



Recommand Product













Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2007, we are professional for make AC and DC electric items such as cable gland,MC4 Connector, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Indicator lamp,Solar Charge Controller,Industrial plug and socket,Meter Socket,Wind Turbine, Terminal Block,Solar product and so on.
- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.
- Golden is always striving hard to provide the best services and competitive price to all customers.

FAQ

1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China - more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the world-class companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

2) Q:Your products?

A: Golden electric is factory for Automatic transfer swithc, Surge protector device, distribution box Enclosure, inverter, DC fuse etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001, SGS etc.

3) Q: Do you have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

4) Q: Your address ?

A: Locates in Guangzhou province, China, welcome to visit us

5) Q:What's the Terminal Block guarantee?

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

6) Q:What's about MOQ? Delivery time?

A: 1pcs for Terminal Block.

7) Q: What's the payment term?A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

8) Q:What's your contact information?

Send us your inquiry !we will reply you in 24 hours!

Guangzhou Golden Electric Co., Ltd.

008618998498109

eva@china-golden.com.cn

chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city, Guangdong province, China