

LCD Solar Regulator Charge Controller MPPT 40A 60A 80A for 12V 24V 36V 48V Solar System

Basic Information

- Place of Origin:
- Brand Name: Golden Electric /OEM

China


IATF16949

workdays

5000/Month

1

- Certification:
- Minimum Order Quantity:
- Carton/Pallet Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Model NO.:
- Current: Package:
- MPK Series 30A/40A/50A/60A/80A/100A 8PCS/CTN
- Package Carton Weight:
- Product Name:
- Charging Mode:

• Package Carton Size:

- Product Weight:
- Voltage:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:

590mm*480mm*300mm 23kg Solar Charge Controller MPPT 2.8kg 12V/24V/48V/Auto

LC, T/T, PayPal, Western Union

Standard Export Carton

8504403090

20000PCS/Month

China

- 135mmx95mmx29mm Golden Or Netural, Or Customer Brand



More Images



Our Product Introduction

Product Description

The solar charge controller is a multi-level maxmium power point tracking (MPPT) photovoltaic battery charge controller with its own technology. Compared with the PWM controller, the MPPT can improve the control accuracy and the output power of the solar panel can be increased by 5% - 30%.

Product Parameters

| Model | MPK40 | MPK40 MPK60 | | MPK80 | MPK100 | | |
|---|------------------|---|----------------|--------------|----------------|-----------------|--|
| Input | | | | | | | |
| Maximum PV open circuit voltage | 150V (at the | 150V (at the lowest temperature),138V (at a standard temperature of 25°C) | | | | | |
| Minimum PV voltage | | 20V/40V/60V/80V | | | | | |
| Rated Charge Current | 30A 4 | A0 | 50A | 60A | 80A | 100A | |
| Output | | | | | | | |
| System Voltage | | 12V/24V/36V/48V/Auto | | | | | |
| Rated Discharge Current | 15A 20A | 2 | 25A | 30A | 40A | 50A | |
| Own consumption | | ≤35mA (48V) | | | | | |
| Mppt highest accuracy | | 99% | | | | | |
| Maximum charging efficiency | | 97% | | | | | |
| Charging control mode | Μι | Multi-stage (MPPT,Absorption,Float,Equalization,CV) | | | | | |
| Float charge | | 13.8V/27.6V/41.4V/55.2V | | | | | |
| Absorption Charge | | 14.4V/28.8V/43.2V/57.6V | | | | | |
| Equalization charge | | 14.6V/29.2V/43.8V/58.4V | | | | | |
| Load disconnection(LVD) | | 10.8V/21.6V/32.4V/43.2V | | | | | |
| Load reconnection(LVR) | | 12.6V/25.2V/37.8V/50.4V | | | | | |
| Load Control mode | Normal, light co | Normal, light control, light and timing control, timing control, reverse light control | | | | | |
| Light control point voltage | | 5V/10V/15V/20V | | | | | |
| Battery type | GEL,SLD,FL | GEL,SLD,FLD and USER(default),Lithium batteries customization 3series 3.7V,4series 3.7V,5series 3.2V | | | | | |
| Other | | | | | | | |
| Human interface | | Color LCD with backlight, 3 buttons | | | | | |
| Cooling mode | | AL alloy heat sink and cooling fan | | | | | |
| Wiring | ≤25 | ≤25mm ² / High current copper terminal ≤25mm ² (3AWG) | | | | | |
| Temperature prode | | line length 3 meters | | | | | |
| Communication mode | | RS485,RJ45 port | | | | | |
| Working temperature range | | -20~+55°C | | | | | |
| Storage temperature range | | -30~+80°C | | | | | |
| Humidity | | 10%~90% No condendation | | | | | |
| Note: Please operate at the ambient ter range of the controller, please derate it. | | the cor | troller. If th | e ambient te | mperature exce | eds the allowab | |

Detailed Photos



Protections Parameters adjustable Battery type RS485/RJ45 port(Optional) Temperature compensation

Our Product Introduction

| Model | MPK40 | MPK60 | MPK80 |
|-----------------------|---------------|---------------|---------------|
| | | | |
| Product Size | 220x200x83mm | 265x220x88mm | 340x240x108mm |
| Mounting hole spacing | 186*126mm- ø5 | 208*170mm-ø5 | 225*245mm-ø5 |
| N.W | 2.5kg | 3.0kg | 4.0kg |
| G.W | 2.8kg | 3.5kg | 4.5kg |
| Set/Carton | 8pcs | 4pcs | 4pcs |
| Weight/Carton | 23kg | 15kg | 18.5kg |
| Measurement | 590x480x300mm | 510x340x320mm | 565x435x375mm |
| Volume/Carton | 0.08CBM | 0.06CBM | 0.09CBM |

Recommand Product



Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2007, we are professional for make AC and DC electric items such as cable gland, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Indicator lamp,Solar Charge Controller,Industrial plug and socket,Wind Turbine, Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

FAQ

1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China - more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the worldclass companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates. 2) Q:Your products?

A: Golden electric is factory for Automatic transfer swithc, Surge protector device, distribution box Enclosure, inverter, DC fuse etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001, SGS etc.

3) Q: Do you have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

4) Q: Your address ?

A: Locates in Guangzhou province, China, welcome to visit us

5) Q:What's the Solar Charge Controller guarantee?

A: 1 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

6) Q:What's about MOQ? Delivery time ?

A: 1pcs for Solar charge controller. Normally less than 100PCS with stock, quick support.

7) Q: What's the payment term?

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

8) Q:What's your contact information ?

Send us your inquiry !we will reply you in 24 hours !

