

Outlet 16mm/19mm/22mm Emergency Stop Push Button Switch with CE and RoHS Certification

ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001,

Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15

LC, T/T, PayPal, Western Union

Basic Information

- Place of Origin:
- Brand Name: Golden Electric /OEM

China

IATF16949

workdays

5000/Month

22mm

≤20mA

>=2mΩ

360

200

5

80

Intermittent

1

- Certification:
- Minimum Order Quantity:
- Packaging Details: Carton/Pallet
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Color Temperature: Pure White
 Lamp Body Material: Plastic
 Input Voltage(V): 6~220V
 Lamp Luminous Flux(Lm): 60
 Light Source: LED
- Mounting Hole Size:
- Sound Type:
- Working Current:
- Insulation Resistance:
- Mounting: Panel Mounting
- Beam Angle(°):
- Lamp Luminous Efficiency(Lm/W):
- Lamp Power(W):
- CRI (Ra):



More Images









Product Description



행용 (155-83-10 BA 3: 常符号 (反限于BA,BL) 融点欄块 Contact Block 155-83-84 Derivative product BL With Mark (BA,BLOnly) 1: 常开 1NO 2: 常闭 1NC 155-84 Derivative product BL With Mark (BA,BLOnly) 1: 常开 1NO 2: 1常闭 1NC 1: 1位 Nhite 2: - togg 16% 2: -position (Maintained) 3: 2 常用 2NC 3: 2 常用 2NC 3: 2 常用 2NC 1: 1位 Nhite 2: - togg 16% Cogg 16% Cogg 16% 2: 1常闭 1NC 3: 2 常用 2NC 1: 1位 Nhite 2: - togg 16% Cogg 16% Cogg 16% 2: 1常闭 1NC 3: 2 常用 2NC 1: 100 Si 都 Green 3: - togg 16% Cogg 16% 2: 1常闭 1NC 3: 2 常用 2NC 1: 110 Si 都 Green 3: - togg 16% Cogg 16% 2: 1常 11 1NC 3: 2 常 11 1NC 1: 110 Si act gat 16% 2: 18 10 1NO+1NC 5: 18 10 1NO+1NC 5: 18 10 1NO+1NC 1: 111 Si act gat 16% 2: 18 11 10 1NO+1NC 5: 18 11 11 10 1NO+1NC 1: 111 Si act gat 16% 3: 18 10 10 1NO 5: 18 11 11 10 1NO+1NC 1: 111 Si act gat 16% 3: 18 10 10 10

Application



Product Parameters

使用环境条件 Working Environme ① 工作温度: -25-+70℃ Working environment temperature ③ 信存温度: -40-+70℃ Storage temperature ③ 污染等级: 3级 Class of pollution ⑤ 防护等级: IP40/IP65/IP66 Protection grade: IP40/IP65/IP66 ◎ 海拔级限高度: <2000米 Limit height, <2000米 EN 60947-1,G814048.5		ent 主要技术参数 Main Technical Data ◎ 報定绝缘电压: 600V Rated insulation voltage ◎ 約定发热电流: 10A Rated thermal current ◎ 开关额定值: AC-15 Ue:380V/250V, le=4.5A Switch rating DC-13 Ue:220V/110V, le=0.6A ◎ 接触电阻: ≤ 50mA Contact resistance ◎ 推荐扭力: 0.9Nm Recommended torque ◎ 接线面积: 最小(min)1×0.5mm2,最大(Max)2x1.5mm2或(or)1x2.5mm2 Connectable area ◎ 机械寿命: 按钮Pushbutton)≥300×104次ttimes);旋钮(Selector Switch)≥1004次ttimes); Mechanical life ◎ 急停钮(Emergency Stop Pushbutton)≥30×104次(times) ◎ 电气寿命: ≥30×104次 Electrical life ◎ 灯电压极限: 0.8Ue≤U≤1.15Ue Limit voltage(Jamp)			
Photo	Description	Contact	Туре	Color	Contour
LA155-B2-EL31	Flush Button Momentary 平钮 弹簧返回 自复型	1NO 13 14	LA155-B2-EA11	0	
		1NO 13 14	LA155-B2-EA31	۲	
		1NO 13 14	LA155-B2-EA55	0	
		1NC 21 22 1NO 13 14	LA155-B2-EA61	•	
		1NC 21 22	LA155-B2-EA42		1, 243 ped-1-
		1NO 15 14	LA155-B2-EL11	0	10 10 10 11 11
	Extended button	1NO 13 14	LA155-B2-EL31	٠	
	Momentary 一 凸钮 弹簧返回 一	1NO 13 14	LA155-B2-EL55	0	
		1NC 21 22 1NO 13 14	LA155-B2-EL61	•	
	自复型	1NO 13 14 1NC 21 22	LA155-B2-EL42		
	Flush Button	1NO 13 14	LA155-B2-EP11	0	· · · · · · · · · · · · · · · · · · ·
LA155-B2-EP33	Momentary (with water-	1NO 13 14	LA155-B2-EP21	٠	
	proof cover) Unmarked	1NO 13 14 1NO 13 14	LA155-B2-EP33	•	and a second sec
	IP 65 平钮(防水罩) 弹簧返回	1NO 13 14	LA155-B2-EP61	•	
	自复型	1NC 21 22	LA155-B2-EP42	۲	day.
LA155-B2-EA3341	Flush Button	1NO 13 14	LA155-B2-EA3341	0	* ************************************
	Momentary Marked 一 平钮(带符号) — 弹簧返回 自复型 一	1NO 13 14	LA155-B2-EA3351	0	
		1NO 13 14	LA155-B2-EA5331		
		1NC 21 22 1NC 21 22	LA155-B2-EA4322 LA155-B2-EA4342	0	
	Extended button Momentary Marked 凸钮(带打号) 洋黃返回 白复型	1NO 13 14	LA155-B2-EL3341	0	a
		1NO 13 14	LA155-B2-EL3351	0	
LA155-B2-EL3361		1NO 13 14	LA155-B2-EL5331	•	10 00 E E
		1NC 21 22	LA155-B2-EL4322	0	
		1NC 21 22	LA155-B2-EL4342	۲	the second secon
	Mushroom button	1NO 13 14	LA155-B2-EC21	•	43 - 34 - 34 - 34 - 34 - 34 - 34 - 34 -
	Momentary — 蘑菇头按钮 弹簧返回	1NO 13 14	LA155-B2-EC31	٠	100 000 000 000 000 000 000 000 000 000
	自复型 -	1NC 21 22	LA155-B2-EC42		
1155-B2-EC42 040	ð	1NO 13 0 14	LA155-B2-ER21		× + + + + + +
	Mushroom button Momentary	110 13 14	CATOP DE CRET	•	
	蘑菇头按钮 弹簧返回	1NO 13 14	LA155-B2-ER31	٠	
155-B2-ER42 Φ6	自复型 - Ф60	1NC 21 22	LA155-B2-ER42		
		PERSONAL TRANSPORT	11 No. 199 199 199 199 199 199 199 199 199 19		-679)
kplanation of T ample(示例):	ype Designatio	n(型号命名方式解释)		221	224
155-B2 - EA	3 1	1 = 1NO 2 = 1 4 = 2NC 5 = 1		100 C 100	334 · 432 😳 335 🛈 533 🐡 434 🚭
		0	• •	•	0
				in commenced	5 = Yellow(黄) 6 = Blue(蓝)
A155-B2 Series		EA Flush Pust 平钮(自复	Contraction of the second s		on,Mushroom(Momentary,Φ40) 西(自复型,Φ40)
A155-B2 系列 A155-B2 系列		EL Extended I 凸钮(自复 EP Flush Push	Pushbutton(Momentary) E	R Pushbutto 蘑菇头按钉	五日夏至(2,040) pn,Mushroom(Momentary,Φ60) 五(自复型,Φ60)

RELATED PRODUCT



If you are interested in our products, please feel free to contact with us, we will try our best to meet your demand.

Packaging & Shipping

Packing:Standard export carton.

Shipping: 1.By Air or by Sea for batch goods, Airport/ Port receiving;

2. Customers specifying freight forwarders or negotiable shipping methods!



Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2017, we are professional for make AC and DC electric items such as isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.



MAIN PRODUCT



Q:How and how long can I get a sample to check your quality?

A: After price confirmation, you can require for samples to check our quality. Then after you send us confirmed files, the samples will be ready for delivery in 7 days. The samples will be sent to you via express and arrive in 5-7 workdays.

Q:How to order our product ?

A: 1).Please tell us the model and quantity and other request you need.

2).We make the PI for you.

- 3).After you confirm the PI, we arrange the order for you after receiving your payment.
- 4). After the goods finished, we send the goods out to you and tell you the tracking number.

5).We will track your goods until you receive the goods.

Q: Can I have a visit to your factory before the order?

A: Welcome! Our factory address: Dongan Industrial Zone, Yueqing City, Wenzhou, Zhejiang, China (Mainland)

Q: What's your shipment method?

A: We ship by Express, by air, by sea, by train. Normally we checked and compare, then provide customer the most proper shipment method.

Q: What's about MOQ?

A: First order MOQ=1pcs

Q: If i want to release order, what's the payment method you accept ?

A: We accept T/T, Paypal, Western union, etc.

Q: If i want to release order, what's the process?

A: Thanks. You can send inquiry to us by alibaba, or send us by email, we will reply within 24hrs.

Our commitent

BETTER PRICE than other sellers for you because of Factory Direct Sale. BETTER QUALITY than before caused by our 10+ years trading experience. STOCK IN TRADE always own to our Fast & Professional production line. FAST DELIVERY always made by our GROUP's Enthusiam. TIMING REPLY in 24 hours all about our TEAM's Passion & Patience. Send your Inquiry Details in the Below, Click "Send" Now~ YOUR BENEFITS IS OUR BUSINESS!!!



008618998498109

eva@china-golden.com.cn

Chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city,Guangdong province,China