

# Matte Painted Solar Energy System Floodlight IP66 Water Proof Solar LED Outdoor Light

ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001,

Peak Season Lead Time: more than 12

LC, T/T, PayPal, Western Union

months Off Season Lead Time: within 15

# **Basic Information**

- Place of Origin:
- Brand Name: Golden Electric /OEM

China

IATF16949

workdays

5000/Month

1

- Certification:
- Minimum Order Quantity:
- Packaging Details: Carton/Pallet
- Delivery Time:
- Payment Terms:
- Supply Ability:



# **Product Specification**

- Technics:
- Illumination Time:
- Cell Type:
- Charging Time (H):
- Usage:
- IP Rating:
- Voltage:
- With Light Source:
- Type:
- Working Mode:
- Working Temperature:
- CCT:
- Working Lifetime:
- Solar Panels:
- Keyword:
- Painted Matte 10-20h LiFePO4 Lithium Battery 4-5h Garden, Street IP66 12/24V With Light Source Solar Flood Light Optically Control/Remote Control 20-60 Degree 3000K-6500K 50, 000h Mono-Crystalline



# More Images





Highlight Solar Flood Lighting





### **Product Description**

# Solar outdoor flood light Outdoor garden use waterproof flood lighting 60W 100W 150W 200W

The home series floodlights are suitable for outdoor use to avoid wiring, and the advantages of zero installation are spread throughout every home. This new type of solar flood light introduced by our company has 180-degree human body induction, and the induction is 8-10M. Traditionally dominated by polycrystalline solar panels, our design prefers to use high-efficiency monocrystalline solar panels, which converts electrical energy faster. It is easy to disassemble, easy to maintain, and more worry-free. The waterproof level is IP66, which can better prevent foreign objects from invading, completely prevent dust from entering, and can withstand strong rainstorm impact. The shell adopts 1.2MM thick die-casting aluminum shell, which is better than the traditional compression resistance and the sectional heat dissipation is faster. In addition, we also designed an intelligent light control mode, which automatically charges during the day and lights automatically at night to meet a variety of usage needs.

### **Main Components**

Monocrystalline silicon solar panel High Luminoud LED Intelligent controller High Quality Lthium Iron Phosphate battery.

## Product Features



# 1.Separated type design

Separate the solar panel and lights for more installation situations and maximum coversion of the sunshine

#### 2.Brand accessories

Adopt brand lifepo4 battery cell with more than 2000 life cycles.

#### 3.Intelligent system

Subverting the previous mechanical design,more sleek lines,more outstanding and upmarkets shape.

#### 4.7 working mode

Sensor/ Semi-induction/ 100%lighting mode/ 50%lighting mode/ 3-Hours lighting mode/ 5-Hours lighting mode/ 8-Hours lighting mode.

#### 5.Effiicient solar panel

Adopt high efficiency monocrystalline silicon solar panel for better performance especially in the cloudy and rainy days.

### 6.Human radar induction


The interference of high harmonics and other clutter can be supperessed effectively.

### **Product Parameters**

| Product Model    | GD-E1         | GD-E2         | GD-E4         | GD-E6               |  |
|------------------|---------------|---------------|---------------|---------------------|--|
| LED Power        | 60W           | 100W          | 150W          | 200W                |  |
| Lumen            | 300Lumen      | 600Lumen      | 1000Lumen     | 1800Lumen           |  |
| Solar Panel      | 8W            | 15W           | 25W           | 40W                 |  |
| Battery Capacity | 3.2V 6000mAH  | 3.2v 12000mAH | 3.2V 18000mAH | 30000mAH            |  |
| Lamp Size        | 179*145*49mm  | 245*165*60mm  | 275*210*80mm  | 308*239*81mm        |  |
| Panel Size       | 215*230*17mm  | 240*400*17mm  | 360*400*20mm  | 280*400*17mm * 2pcs |  |
| Package          | 10sets/ctn    | 8sets/ctn     | 5sets/ctn     | 4sets/ctn           |  |
| Carton Size      | 503*355*247mm | 515*425*265mm | 420*405*385mm | 458*330*428mm       |  |
| G.W/CTN          | 24.5KG        | 24.2KG        | 30.8KG        | 26.1KG              |  |
| IP Class         | IP66          |               |               |                     |  |
| Charging Time    | 4-5H          |               |               |                     |  |
| Working Time     | 10-20H        |               |               |                     |  |
|                  |               |               |               |                     |  |

| Femperature  |   |  |  |  |  |  |
|--|---|--|--|--|--|--|
| Main Material  | (CW)-(6000-6500K)   |  |  |  |  |  |
| Cable  | Die-casting aluminum+tempered glass 1.5m cable + 2m extension cable   |  |  |  |  |  |
| Color  | 1.5m cable + 2m extension cable White   |  |  |  |  |  |
| Working Mode   | 100% lighting mode/ 50% lighting mode/ 3-Hours lighting mode/ 5-Hours lighting mode/ 8-Hours lighting mode.                                   |  |  |  |  |  |
| Detailed Photos  |   |  |  |  |  |  |
| Packing  |   |  |  |  |  |  |
| Surface frame<br>Lamp beads<br>Sensor Mod<br>Vaterproof rubber r |   |  |  |  |  |  |
| Explosion-proof gl   | ass Lamp housing  |  |  |  |  |  |
|  | proof rubber rings with multiple waterproof protection and thunderstorms resistance<br>assembly to solve maintenance problems without worries |  |  |  |  |  |
|  | proof rubber rings with multiple waterproof protection and thunderstorms resistance   |  |  |  |  |  |












**Recommand Product** 



## **Company Profile**

- Golden Electric Co.,Ltd ,was foundad in 2007, we are professional for make AC and DC electric items such as cable gland,Solar PV Cable, MC4 Connector, isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Indicator lamp,Solar Charge Controller,Industrial plug and socket,Wind Turbine, Solar product and so on.



| Guangzhou Golden Electric Co., Ltd.  |                 |                         |                  |  |  |  |
|--|-----------------|-------------------------|------------------|--|--|--|
| C  | 008618998498109 | eva@china-golden.com.cn | Chinagoldene.com |  |  |  |
| Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,<br>Guangzhou city,Guangdong province,China |                 |                         |                  |  |  |  |