

# US 10/Piece Samples Requested Safety Class II Mc4 Solar Cable Connector Crimping Tool

ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001,

Peak Season Lead Time: more than 12

LC, T/T, PayPal, Western Union

months Off Season Lead Time: within 15

# **Basic Information**

- Place of Origin:
- Brand Name: Golden Electric /OEM

China

IATF16949

workdays

5000/Month

Blue

3 Years

1

- Certification:
- Minimum Order Quantity:
- Packaging Details: Carton/Pallet
- Delivery Time:
- Payment Terms:
- Supply Ability:



# **Product Specification**

Color:

. Length:

- Warranty:
- Insulation Material:
- Rated Current:
- Temperature Range:
- Safety Class:
- Rated Voltage:
- Contact Material:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:
- PPO 25-30A -40~+125 270mm II Of Mc4 Solar Cable Connector DC1000V Copper, Silver Plated Box Half-Box Joint Golden Electric Or Customize China 8537209000 5000/Month



### More Images









### About us:

GUANGZHOU GOLDEN ELECTRIC CO.,LTD has 10 years of experience in photovoltaic cable production. The company has passed ISO9001 management system certification. The photovoltaic cable series has passed the German TUV and China CQC certification. Certificate covers 1.5sqmm-25sqmm. Our product is produced by special photovoltaic materials, using advanced electron beam irradiation cross-linking technic. Our product can be used for a long time in an environment of minus 40 degrees, and with strong UV resistance. Main Products: Photovoltaic cables, Photovoltaic connectors, PV Junction Box, Solar PV connectors, solar photovoltaic Controllers, PV inverters for solar energy, photovoltaic systems, batteries, etc.

**Product Description** 





\*Applicable for non-welding andslandard electric connection newleverage design savesatleast 35% energy compared to common crimpingtools.

\*Precise crimping diesets and integrallock with sefreleasingmechanismensurehigh-qualitycrimping effectafter crimping repeatedly

\*All the kevparts of the enerays aving crimpinatools have been specially harden. The toals are with the features of hiah effectiveness and longuing lifetime

\*Favorable balanceof the barycenter,anglepresstop andhande shape designmeeting human beingengneering principlemake the operation easier and convenient

应用范围	端子		and a second second second	部口	压模类型
Range of Application	Connectors	mm	AWG	Die set	Profile
裸端子 (欧式W 型坑压) Non-insulated terminals	88	1.0-16	20-5		V
裸護子 旧式点団 Non-insulated terminals	88	1.0-1.0 1.5-2.5 4.0-6.0 10.0	17-7		V
非预绝缘开放 式插塞端子 Non-insulated tobs and receptacles	Ø	0.5-1.0 1.5-2.5 4.0-6.0	20-10		M
超線和非絕缘套 管式譜子 (樹形圧接) Insulated and non-insulated ferrules	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	0.5 0.75 1, 1.5 2.5,4	20-12		
候诺子 闭端子日式方 点坑压 Non-insulated terminals	88	0.5-1.0 1.5-2.5 4.0-6.0 10.0	20-7	and an and	V
同轴电缆 Rg58, 59, 62, 8X, 140, 142, 174, 210,223,303, 400, BBER OPTIC' BELDEN 8279	<b>6</b> 30°	6.5 5.5 4.1 3.3 3.0 1.7			
同轴电缆 RG55 58,59,62,140, 141,142,223,303,400, FIBER OPTIC, BELDEN 8279	<b>6</b> 39°	6.5 5.4 1.72			
問轴电缆 RG55,58,59,62,5,6, 21,140,141,142, 143,210,212,222,223, 303,304,400, BELDEN 8279,8281, 9231,9141	<b>6</b> 30°	8.1,6.5 5.4,2.6 1.72			
Parameters					
			J		
type MC4 so	olar crimp	ing too	bl		
	Range of Application   複選子 (取式W型坑臣) Non-insulated terminals   提調子 (ID式点面) Non-insulated terminals   非預態錄开放 式语蓋能子 Non-insulated terminals   總和非絶缘套 管式消子 (NE形压接) Insulated and non-insulated ferrules   總集和非絶缘套 管式消子 (NE形压接) Insulated and non-insulated terminals   標調子 (IDI器子曰式方 点沉面) Non-insulated terminals   同轴电缆 Rg55, 59, 62, SX, 140, 142, 174, 210, 223, 303, 400, RBE CPTIC BELDEN 8279   同轴电缆 RG55,58,59,62,56, 21,140,141,142, 143,210,212,222,223, 303,304,400, BELDEN8279, 8281, 9231,9141	Range of Application   Connectors     提試子 (取式W型坑臣) Noninsulated terminals   よいの、     提試子 (取式局面) Non-insulated terminals   よいの、     非预理錄开放 式语重裝子 Non-insulated terminals   よいの、     提協和非總錄在 管式調子 (NB形压度) Insulated and noninsulated ferrules   よいの、     提協和非總錄在 管式調子 (NB形压度) Insulated and noninsulated terminals   よいの、     提協和非總錄在 管式調子 (NB形压度) Insulated and noninsulated terminals   よいの、     開始平式気力 (AST) (AST) (AST) (AST) (AD	Range of Application   Connectors   mm'     標選子 IRTRW型的ED Non-insulated terminals   Image: Connectors   1.0-16     提購子 IRTR@SP Insulated terminals   Image: Connectors   1.0-16     #展開子 Insulated terminals   Image: Connectors   1.0-16     #展開子 Insulated and non-insulated terminals   Image: Connectors   1.0-16     提集和事程檔案 管式調子 Insulated and non-insulated terminals   Image: Connectors   1.0-16     提集和事程檔案 管式調子 Insulated and non-insulated terminals   Image: Connectors   0.5-1.0     Image: Connectors   Image: Connectors   Image: Connectors     Image: Connectorselaten   Image: Connectorselaten	Range of Application   Connectors   mm*   AWG     提選子 [IRXTW 型店店] Non-insulated terminals   Image: Connectors   1.0-16   20-5     提選子 [IRXTGE] Non-insulated terminals   Image: Connectors   1.0-10   1.0-10   1.7-7     #預塑錄开放 TdT # 整整 TdT # 整整 TdT # 整整 Table # The State terminals   Image: Connectors   0.5-10   1.7-7     # TD # \$FT # 50 Non-insulated tabs and receptocles   Image: Connectors   0.5-10   1.7-7     # WE # 50 To Table # 50 Table # 50 Tabl	Renge of Appleation   Connectors   mm   AWG   Disset     Witt F Rex.Tw. Birking Non-insulted Heimings   Soft Soft   1.0-16   20-5   Soft Soft Soft Soft Soft Soft Soft Soft

Crimping range 2.5mm2, 4.0mm2, 6.0mm2

Length 270mm

Weight 0.9kg

Product features:

- 1. For solar connector, MALE and FEMALE pins
- 2. For solar cable size: 14 / 12 / 10AWG ( 2.5 / 4 / 6 mm2)
- 3. Emergency release switch to release cable
- 4. High precision ratchet mechanism for complete crimps
- 5. 1.2 tons pressure at crimping face with minimal hand effort
- 6. Interchangeable high precision crimping die set
- 7. Interchangeable locator for precision positioning of terminals

#### Features:

- \* Good quality.
- \* Interchangeable high-precision crimping die set;
- \* 1.2 metric tons pressure at crimping face, with minimal hand effort;
- \* Solar Crimping Tool is High-precision ratchet mechanism for complete crimps

### Specification:

Name: Solar PV Tools Kits for MC3/MC4 Solar Connectors With Crimping+Stripping+Cutting Model: 572497

Material: metal + Acrylonitrile Butadiene Styrene(ABS) + Nylon

Product Description: Solar PV Tools Kits for MC3/MC4 Solar Connectors With Crimping+Stripping+Cutting Solar Crimping Tools Parameters(MC4 type):

Length:220mm Weight:0.93Kg AWG:26-10AWG Capacity:2.5-6mm2 Stripper Parameters: Length: 165mm Weight: 0.16Kg Automatic rebound spring No damaging of the conductor core For cutting wire, 30mm max. Stripping wire 0.9-6.0 mm2

### Provide you with many options





Q1: Are you a factory or trading company

A1: We are a factory, we can guarantee our price is first-hand, very cheap and competitive.

Q2: How does your factory do regarding quality control?

A2: All the products will be 100% checked before the shipment

Q3: When can I get the price?

A3:Usually we quote within 24 hours after we get your inquiry.

Q4: How could I get a sample?

A4: if you can not buy our product in your local area, we will ship a sample to you. You will be charged a sample price plus all related shipping costs. Express delivery charge depends on the quantity of the samples.

Q5: What is the price of shipping?

A5: Depending upon the port of delivery, prices vary.

# Any more query please contact with us, thank you!

