



Round Wire Concentric Cable with 2X8 AWG Aluminum Conductor and 70C Rated Temperature

Our Product Introduction


Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months
Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month



Product Specification

- Material Shape: Round Wire
- Range Of Application: Round Wire
- Brand: Industrial
- Voltage: 450/750V
- Conductor: Tinner Copper; CCC; CCA; Pure Copper
- Core Color: Black
- Rated Temperature: 70, 90, 105
- Length: 100m/100y/or As Require
- Number Of Cores: Single Core- Multicores Power Cable
- Sheath: Flexible PVC
- Characteristics: Light Weight, High Conductivity
- Size: Customized Size
- Delivery: 7-12days
- Sample Time: 3-5days
- Current: AC Cable



More Images



for more products please visit us on chinagoldene.com

Product Description

Product Description



Terms:

- 1.OEM is welcomed
- 2.ISO/CE/ETL/ROHS/UL/SONCAP and other certifications are available
- 3.Competitive price and high quality offered.
4. Best service for you!

Basic Info:

1. Name: : Electric Wire/ Electric Cable/Power Cable/Single Cable/ Flat Cable/ Flexible Cable
2. Structure: Conduct---pure copper/copper clad copper/copper clad aluminum
Insulation---blue/yellow/pink/grey/others you like
3. Size:According to Standard/Sample/Customer's request.
4. The material of the inner conductor and outer sheath materials in accordance with customer requirements.

Product Description:

Intruduction of the Electric Wire PVC Insulated Single Core H05V-U / H07V-U/ H07V-R wire:

- 1, The national certification of qualified manufacturers
- 2, Standard: GB 5023.1, IEC 60227/228, VDE
- 3, CE, RoHS, ISO ,SGS Certificate
- 4, Meet European standards and can be customized according to customer requirements
- 5, OEM, ODM cooperation

PVC insulation flexible wire

Applications:

harmonized PVC European single-conductor hook-up wires with a solid bare copper core. Ideal for the internal wiring of appliances, apparatus, switchboards and distributor boards or where a solid core is required. Suitable in dry rooms for fixed and flexible laying. May be used for exposed and embedded conduits. Found in electronic and electrical equipment and switchgear cabinets designed for export to a European country for MRO replacement of European made equipment wire. The products is suitable for use in power installations, fixed wiring or flexible connections for electrical appliances, Like lighting, electronic equipment, instrument and communication equipment with rated voltage 300/500V, 450/750V, The Operating temperature: Allowing the wire of work for long time should not exceed +70 centigrade.

SPECIFICATIONS:


Nominal cross sectional area of conductor (mm ²)	Insulation Thickness (mm)	Sheath Thickness (mm)	overall diameter of cable (mm)	Approx.weight of cable(kg/km)		Max.D.C resistance of conductor(ohm/km)		Testing voltage A.C (kV/min)
				Cu	Al	Cu	Al	
1*2.5	0.7	1.4	6.1	57	41	7.41	12.1	3.5
1*4	0.7	1.4	6.6	74	50	4.61	7.41	3.5
1*6	0.7	1.4	7.1	96	59	3.08	4.61	3.5
1*10	0.7	1.4	8.2	138	79	1.83	3.08	3.5
1*16	0.7	1.4	9.2	198	103	1.15	1.91	3.5
1*25	0.9	1.4	10.7	294	144	0.727	1.2	3.5
1*35	0.9	1.4	11.7	387	178	0.524	0.868	3.5
1*50	1	1.4	13.2	510	226	0.387	0.641	3.5
1*70	1.1	1.4	15.1	712	302	0.268	0.443	3.5
1*95	1.1	1.5	16.9	963	395	0.193	0.32	3.5
1*120	1.2	1.5	18.5	1197	480	0.153	0.253	3.5
1*150	1.4	1.6	20.7	1476	591	0.124	0.206	3.5
1*185	1.6	1.6	22.8	1829	722	0.0991	0.164	3.5
1*240	1.7	1.7	25.4	2375	920	0.0754	0.125	3.5
1*300	1.8	1.8	28	2957	1131	0.0601	0.1	3.5
1*400	2	1.9	31.6	3762	1428	0.047	0.0778	3.5
1*500	2.2	2	35.1	4795	1798	0.0366	0.0605	3.5
1*630	2.4	2.2	39.3	6171	2295	0.0283	0.0469	3.5

01**PVC OR PE JACKET**

High temperature resistance, good aging resistance, good environmental resistance.

**STEEL WIRE OR STEEL-TAPE ARMOR****02**

Use steel wire or steel belt armor to increase the compressive strength of the cable.

**03****STABLE PERFORMANCE**

Stable power transmission performance and long service life.




GOOD FLEXIBILITY

04



The armor layer on the cable can enhance the tensile strength and has good flexibility.



PRINTING WAYS



Application



Household Wiring



Security & Protection System



Intelligent safe-guard system



audio system



fire fighting system



Industrial construction

MAIN PRODUCTS



Packaging & Shipping

Packaging & Shipping

Packing : Steel wooden drum (fumigation) Cable length in each drum: 1000m/2000m or as per actual cable length requirements. Drum size: As per cable length and container size *In order to quote you accurate price, kindly tell us your needed

cable length quantity. Larger quantity, more discount benefit ready for you! Shipping Port:Tianjin, Qingdao, or other ports as per

your requirements. Sea freight:FOB/C&F/CIF quotation are all available. *For some countries such as Africa countries, middle east

countries, our sea freight quotation is much cheaper than clients get from local shipping agency.



Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2017, we are professional for make AC and DC electric items such as isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.



Related Products



FAQ

Q:How and how long can I get a sample to check your quality?

A: After price confirmation, you can require for samples to check our quality. Then after you send us confirmed files, the samples will be ready for delivery in 7 days. The samples will be sent to you via express and arrive in 5-7 workdays.

Q:How to order our product ?

A: 1).Please tell us the model and quantity and other request you need.
2).We make the PI for you.
3).After you confirm the PI, we arrange the order for you after receiving your payment.
4).After the goods finished, we send the goods out to you and tell you the tracking number.
5).We will track your goods until you receive the goods.

Q: Can I have a visit to your factory before the order?

A: Welcome! Our factory address: Dongan Industrial Zone,Yueqing City, Wenzhou, Zhejiang, China (Mainland)

Q: What's your shipment method?

A: We ship by Express, by air, by sea, by train. Normally we checked and compare, then provide customer the most proper shipment method.

Q: What's about MOQ?

A: First order MOQ=1pcs

Q: If i want to release order, what's the payment method you accept ?

A: We accept T/T, Paypal, Western union, etc.

Q: If i want to release order, what's the process?

A: Thanks. You can send inquiry to us by alibaba, or send us by email, we will reply within 24hrs.

Our commitent

BETTER PRICE than other sellers for you because of Factory Direct Sale.
BETTER QUALITY than before caused by our 10+ years trading experience.
STOCK IN TRADE always own to our Fast & Professional production line.
FAST DELIVERY always made by our GROUP's Enthusiam.
TIMING REPLY in 24 hours all about our TEAM's Passion & Patience.
Send your Inquiry Details in the Below, **Click "Send" Now~**
YOUR BENEFITS IS OUR BUSINESS!!!



Guangzhou Golden Electric Co., Ltd.



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,
Guangzhou city,Guangdong province,China