



Bakelite Base Material TC Series Electrical Fixed Terminal TC-4004 for Wire Connection

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months
Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month



Product Specification

- Character: Environmental Protection
- Production Process: Injection Molding
- Brand: Golden Or Natural Or Customer Brand
- Product Name: Barrier Terminal Blocks
- Wire Range: 22-14AWG
- Usage: Wire Connecting
- Rated Voltage: 600V
- Rated Current: 60,100,150,200,300,400,600A
- Conductor Material: Copper
- Model No.: Tc Series
- Transparent Cover Material: As Resin
- Base Material: Bakelite
- Transport Package: Standara Export Carton
- Specification: 2P/3P/4P
- Trademark: Golden Electric Or Customize



More Images



for more products please visit us on chinagoldene.com

Product Description

Product Description

TC Series Connectors Terminals Blocks

1. Adopting thermosetting plastics, the safety factor of high current is more reliable, structure parts adopt plate screw clamping technology, rated AC voltage is 600V, rated current of conducting strips is as following:

60A, 100A, 150A, 200A, 300A, 400A, 600A, the range of wire section is from 10mm to 300mm.

2. It can be divided into 3P 4P flat screw installation according to arrangement, it will be more reliable by using together without terminations, it can be used for connecting high current of kinds of electric devices.



1. The outer casing is made of thermosetting plastics.
2. Copper conductor, good electrical conductivity, nickel-plated anti-corrosion.
3. Dust-proof and transparent plastic protective cover for durability.

Product Parameters

| Mode No | Wire Section | Rated Current/Voltage | Insulation resistance | Base Material | Transparent cover | Conductor Material | Flame level | Screw type/torque | L/W/H(mm) |
|---------|-----------------------|-----------------------|-----------------------|---------------|-------------------|--------------------|-------------|-------------------|---------------|
| TC-603 | 6-14mm ² | 60A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M6 2.8-4 | 85.5/43/31.5 |
| TC-604 | 6-14mm ² | 60A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M6 2.8-4 | 114.5/43/31.5 |
| TC-1003 | 10-22mm ² | 100A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M6 6-8 | 102.5/55/36 |
| TC-1004 | 10-22mm ² | 100A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M6 6-8 | 137.5/55/36.5 |
| TC-1503 | 10-50mm ² | 150A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M8 6-12 | 115/66/39.5 |
| TC-1504 | 10-50mm ² | 150A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M8 6-12 | 153.5/66/39.5 |
| TC-2003 | 25-70mm ² | 200A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M8 6-12 | 132.5/72/44 |
| TC-2004 | 25-70mm ² | 200A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M8 6-12 | 176/72/44 |
| TC-3003 | 35-150mm ² | 300A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M10 15-20 | 165/90/51.5 |

| | | | | | | | | | | |
|------------|--------------------|-----------|--------|----------|----------|-------|------------|-----|-------|-------------|
| TC-35-3004 | 150mm ² | 300A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M10 | 15-20 | 220/90/51.5 |
| TC-35-4003 | 185mm ² | 400A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M10 | 15-20 | 165/90/51.5 |
| TC-35-4004 | 185mm ² | 400A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M10 | 15-20 | 220/90/51.5 |
| TC-50-6003 | 300mm ² | 600A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M12 | 25-35 | 206/100/70 |
| TC-50-6004 | 300mm ² | 600A/600V | >100MΩ | Bakelite | AS resin | Brass | UL94 V0-V2 | M12 | 25-35 | 275/100/70 |

Provide you with many options

Tc series:

| | | | |
|--|--|---|---|
|  |  |  |  |
| TC-2004 导线截面wire section: 100mm ² 额定电流/电压 rated current/voltage: 200A/600V 长/宽/高length/wide/high: 177.5/71/44mm | TC-2005 导线截面wire section: 100mm ² 额定电流/电压 rated current/voltage: 200A/600V 长/宽/高length/wide/high: 224/72.7/46.2mm | TC-3003 导线截面wire section: 150mm ² 额定电流/电压 rated current/voltage: 300A/600V 长/宽/高length/wide/high: 165/90.5/52.5mm | TC-3004 导线截面wire section: 150mm ² 额定电流/电压 rated current/voltage: 300A/600V 长/宽/高length/wide/high: 220/90.5/52.5mm |
|  |  |  |  |
| TC-4003 导线截面wire section: 200mm ² 额定电流/电压 rated current/voltage: 400A/600V 长/宽/高length/wide/high: 165/90.5/52.5mm | TC-4004 导线截面wire section: 200mm ² 额定电流/电压 rated current/voltage: 400A/600V 长/宽/高length/wide/high: 220/90.5/52.5mm | TC-6003 导线截面wire section: 300mm ² 额定电流/电压 rated current/voltage: 600A/600V 长/宽/高length/wide/high: 207/100.5/75.5mm | TC-6004 导线截面wire section: 300mm ² 额定电流/电压 rated current/voltage: 600A/600V 长/宽/高length/wide/high: 275/100.5/75.5mm |

Tb series:

| | | | |
|--|--|---|---|
|  |  |  |  |
| TB-2505 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 25A/600V 长/宽/高length/wide/high: 79/30/19mm | TB-2506 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 25A/600V 长/宽/高length/wide/high: 91/30/19mm | TB-2510 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 25A/600V 长/宽/高length/wide/high: 139/30/19mm | TB-2512 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 25A/600V 长/宽/高length/wide/high: 163/30/19mm |
|  |  |  |  |
| TB-3503 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 35A/600V 长/宽/高length/wide/high: 55/30/19mm | TB-3504 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 35A/600V 长/宽/高length/wide/high: 67/30/19mm | TB-3506 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 35A/600V 长/宽/高length/wide/high: 91/30/19mm | TB-3512 导线截面wire section: 0.5-2.5mm ² 额定电流/电压 rated current/voltage: 35A/600V 长/宽/高length/wide/high: 165/30/19mm |
|  |  |  |  |
| TB-4503 导线截面wire section: 1.5-4mm ² 额定电流/电压 rated current/voltage: 45A/600V 长/宽/高length/wide/high: 70/38/23.5mm | TB-4504 导线截面wire section: 1.5-4mm ² 额定电流/电压 rated current/voltage: 45A/600V 长/宽/高length/wide/high: 86/38/23.5mm | TB-4505 导线截面wire section: 1.5-4mm ² 额定电流/电压 rated current/voltage: 45A/600V 长/宽/高length/wide/high: 103/38/23.5mm | TB-4506 导线截面wire section: 1.5-4mm ² 额定电流/电压 rated current/voltage: 45A/600V 长/宽/高length/wide/high: 120.5/38/23.5mm |

Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2007, we are professional for make AC and DC electric items such as cable gland, isolator switch , fuse and fuse holder, Circuit breaker , distribution box , PV combiner box ,surge protector, Timer Switch,Industrial plug and socket,Wind Turbine, Solar product,

busbar clamp and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The products sell well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

FAQ

1)Q:How can i trust your company?

A:Golden electric is The top 10 manufacture in China - more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the world-class companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

2) Q:Your products?

A: Golden electric is factory for Circuit Breaker, Automatic transfer switch, Surge protector device, distribution box Enclosure, inverter, DC fuse, busbar clamp etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001 ,SGS etc.

3) Q: Do you have forwarder?

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

4) Q: Your address ?

A: Locates in Guangzhou province, China,welcome to visit us

5) Q:What's the Fuse, Fuse holder guarantee?

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

6) Q:What's about MOQ? Delivery time ?

A: 1pcs for Fuse holder.

7) Q: What's the payment term?

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

8) Q:What's your contact information ?

Send us your inquiry !we will reply you in 24 hours !



Guangzhou Golden Electric Co., Ltd.



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,
Guangzhou city,Guangdong province,China