




## T8-0609 T8-0812 Series Electrical Busbar Copper Terminal Block for Customized Request

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month




### Product Specification

- Character: High Temperature Resistance
- Production Process: Injection Molding
- Brand: Golden Or Natural Or Customer Brand
- Product Name: Barrier Terminal Blocks
- Wire Range: 0.5-10mm<sup>2</sup>
- Usage: Wire Connecting
- Rated Voltage: 600V
- Rated Current: 15A 25A 45A 60A 100A
- Conductor Material: Copper
- Model No.: Terminal Block T8-0609
- Transparent Cover Material: As Resin
- Base Material: Bakelite
- Application: Tpcb, Cable, Push-Pull Connection, Computer, Comm:
- Transport Package: Standara Export Carton



### More Images



for more products please visit us on [chinagoldene.com](http://chinagoldene.com)


## Product Description

## Product Description

**Material:**


- PA, Polyamide 66, 94-2 grade. Inflaming retarding. Working Temperature: -30°C to 110°C
- ABS, good resist dissolve, good bounce impact fore. Working Temperature: -20°C to 70°C
- PE, Polypropylene, Inflaming retarding, low transparency, low rigidity, good bounce impact force. Working Temperature: -30°C to 110°C
- Brass, screw: iron plated zinc
- Voltage: 250V-450V
- Color: according sample picture or customized

## Product Parameters

**T8-0609 Series**

Way Install Size (L) mm Outer Size (L1) mm Section cross of brass (mm<sup>2</sup>)

|    |      |            |     |
|----|------|------------|-----|
| 4  | 48.2 | 59.2*11.2  | 6*9 |
| 6  | 65.4 | 76.4*11.2  | 6*9 |
| 8  | 82.6 | 93.6*11.2  | 6*9 |
| 10 | 99.8 | 110.8*11.2 | 6*9 |
| 12 | 117  | 128*11.2   | 6*9 |

**T8-0812 Series**

Way Install Size (L) mm Outer Size (L1) mm Sectioncross of brass (mm²)

|    |      |            |      |
|----|------|------------|------|
| 4  | 48.2 | 59.2*12.2  | 8*12 |
| 6  | 65.4 | 76.4*12.2  | 8*12 |
| 8  | 82.6 | 93.6*12.2  | 8*12 |
| 10 | 99.8 | 110.8*12.2 | 8*12 |
| 12 | 117  | 128*12.2   | 8*12 |

Provide you with many options

### Tc series:

|  |  |   |   |
|--|--|---|---|
|   |   |    |   |
| <b>TC-2004</b><br>导线截面wire section: 100mm²<br>额定电流/电压 rated current/voltage: 200A/600V<br>长/宽/高length/wide/high: 177.5/71/44mm   | <b>TC-2005</b><br>导线截面wire section: 100mm²<br>额定电流/电压 rated current/voltage: 200A/600V<br>长/宽/高length/wide/high: 224/72.7/46.2mm | <b>TC-3003</b><br>导线截面wire section: 150mm²<br>额定电流/电压 rated current/voltage: 300A/600V<br>长/宽/高length/wide/high: 165/90.5/52.5mm  | <b>TC-3004</b><br>导线截面wire section: 150mm²<br>额定电流/电压 rated current/voltage: 300A/600V<br>长/宽/高length/wide/high: 220/90.5/52.5mm  |
|   |   |    |   |
| <b>TC-4003</b><br>导线截面wire section: 200mm²<br>额定电流/电压 rated current/voltage: 400A/600V<br>长/宽/高length/wide/high: 165/90.5/52.5mm | <b>TC-4004</b><br>导线截面wire section: 200mm²<br>额定电流/电压 rated current/voltage: 400A/600V<br>长/宽/高length/wide/high: 220/90.5/52.5mm | <b>TC-6003</b><br>导线截面wire section: 300mm²<br>额定电流/电压 rated current/voltage: 600A/600V<br>长/宽/高length/wide/high: 207/100.5/75.5mm | <b>TC-6004</b><br>导线截面wire section: 300mm²<br>额定电流/电压 rated current/voltage: 600A/600V<br>长/宽/高length/wide/high: 275/100.5/75.5mm |

### Tb series:

|  |  |   |   |
|--|--|---|---|
|   |   |    |   |
| <b>TB-2505</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 25A/600V<br>长/宽/高length/wide/high: 79/30/19mm | <b>TB-2506</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 25A/600V<br>长/宽/高length/wide/high: 91/30/19mm | <b>TB-2510</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 25A/600V<br>长/宽/高length/wide/high: 139/30/19mm | <b>TB-2512</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 25A/600V<br>长/宽/高length/wide/high: 163/30/19mm   |
|   |   |    |   |
| <b>TB-3503</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 35A/600V<br>长/宽/高length/wide/high: 55/30/19mm | <b>TB-3504</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 35A/600V<br>长/宽/高length/wide/high: 67/30/19mm | <b>TB-3506</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 35A/600V<br>长/宽/高length/wide/high: 91/30/19mm  | <b>TB-3512</b><br>导线截面wire section: 0.5-2.5mm²<br>额定电流/电压 rated current/voltage: 35A/600V<br>长/宽/高length/wide/high: 165/30/19mm   |
|   |   |    |   |
| <b>TB-4503</b><br>导线截面wire section: 1.5-4mm²<br>额定电流/电压 rated current/voltage: 45A/600V<br>长/宽/高length/wide/high: 70/38/23.5mm | <b>TB-4504</b><br>导线截面wire section: 1.5-4mm²<br>额定电流/电压 rated current/voltage: 45A/600V<br>长/宽/高length/wide/high: 86/38/23.5mm | <b>TB-4505</b><br>导线截面wire section: 1.5-4mm²<br>额定电流/电压 rated current/voltage: 45A/600V<br>长/宽/高length/wide/high: 103/38/23.5mm | <b>TB-4506</b><br>导线截面wire section: 1.5-4mm²<br>额定电流/电压 rated current/voltage: 45A/600V<br>长/宽/高length/wide/high: 120.5/38/23.5mm |

### Company Profile

- Golden Electric Co.,Ltd ,was founded in 2007, we are professional for make AC and DC electric items such as cable gland, isolator switch, fuse and fuse holder, Circuit breaker, distribution box, PV combiner box, surge protector, Timer Switch, Industrial plug and socket, Wind Turbine, Solar product,

busbar clamp and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The products sell well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

#### FAQ

**1)Q:How can i trust your company?**

A:Golden electric is The top 10 manufacture in China - more than 350 Agents in local market and more than 100 foreign clients make OEM,ODM order from us,Golden electric is a big company, we have cooperation with LS, EKF the world-class companies. Our company over 100 employees, products pass CE,IEC,TUV,SAA, RCM, ROHS certificates.

**2) Q:Your products?**

A: Golden electric is factory for Circuit Breaker, Automatic transfer switch, Surge protector device, distribution box Enclosure, inverter, DC fuse, busbar clamp etc. Providing customers very competitive sources, and can be your sourcing agent in China. Goods are following international standards, IE, CE, ISO9001 ,SGS etc.

**3) Q: Do you have forwarder?**

A: Yes, we have good forwarder cooperated over 10 years, they help us import and export . For small package orders, suggest to use by Express.

**4) Q: Your address ?**

A: Locates in Guangzhou province, China,welcome to visit us

**5) Q:What's the Fuse, Fuse holder guarantee?**

A: 2 years warranty. If customer's problem, then customer burden. If our problem, then we send new goods to customer to replace asap.

**6) Q:What's about MOQ? Delivery time ?**

A: 1pcs for Fuse holder.

**7) Q: What's the payment term?**

A: Normally 100% T/T in advanced payment. If big order then about 50% advanced payment, balance before shipment.PAYPAL,WESTERN UNION,CASH for small order .

**8) Q:What's your contact information ?**

**Send us your inquiry !we will reply you in 24 hours !**



**Guangzhou Golden Electric Co., Ltd.**



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,  
Guangzhou city,Guangdong province,China