



Natural Crimp Terminal Tinned Wire Terminal Connector Wire Connector Copper Cable Lug

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month




Product Specification

- Model NO.: E-5 SERIES
- Shape: Tubular
- Interface Type: AC/DC
- Brand: Golden Electric/OEM
- Rated Voltage: 415V
- Entry: Chamfered Entry
- Busbar: -55c~150c
- Size: 1.5~600mm²
- Coating: Tin
- OEM: Accept
- Sample: Accept
- Wire Range: 22~16/16~14/14~12/12~10 A.W.G
- Color: Natural
- Product Key Words: Insulated Terminal Blocks
- Imax: 27A



More Images




for more products please visit us on chinagoldene.com

ITEM NO 型 号	USA Screw 美制螺栓号	Screw dia 螺栓口直径 d2(mm)	Dimension/尺寸(mm)							WIPR RANGE AWG/mm²	Plating	
			W	F	L	E	D	d	T			
RNB5.5-3.5	#6	3.7	7.2	5.9	15.7	6.8	5.6	3.4	1.0	12-10AWG 4-6mm² 48A	Tin	
RNB5.5-4S	#8	4.3	7.2	5.9	15.7							
RNB5.5-4L	#8	4.3	9.5	8.3	19.8							
RNB5.5-5	#10	5.3	9.5	8.3	19.8							
RNB5.5-6	1/4	6.4	12.0	13.0	25.8							
RNB5.5-8	5/16	8.4	15.0	13.7	28.0							
RNB5.5-10	3/8	10.5	15.0	13.7	28.0							
RNB5.5-12	1/2	13.0	19.2	16.0	32.4							
RNB 8-4	#8	4.3	8.8	23.8	9.3	8.5	7.2	4.5	1.2	8AWG 6-10mm² 62A		
RNBS 8-5	#10	5.3	8.8	23.8	11.1							
RNBM 8-5	#10	5.3	12.0	23.8	9.3							
RNBL 8-5	#10	5.3	15.0	29.8	13.8							
RNBS 8-6	1/4	6.4	12.0	23.8	9.3							
RNBL 8-6	1/4	6.4	15.0	29.8	13.8							
RNB 8-8	5/16	8.4	15.0	29.8	13.8							
RNB 8-10	3/8	10.5	15.0	29.8	13.8							
RNB 8-12	1/2	13.0	20.0	33.5	15.0							
RNB 14-4	#8	4.3	12.0	29.8	13.3	10.5	9.0	5.8	1.4	6AWG 10-16mm² 88A		
RNB 14-5	#10	5.3	12.0	29.8	13.3							
RNBS 14-6	1/4	6.4	12.0	29.8	13.3							
RNBL 14-6	1/4	6.4	16.0	32.8	13.3							
RNB 14-8	5/16	8.4	16.0	32.8	14.5							
RNB 14-10	3/8	10.5	16.0	32.8	14.5							
RNB 14-12	1/2	13.0	22.0	41.0	19.5							



叉形裸端子 Non-insulated Spade Terminal

Terminal Material: copper(紫铜)
Brazed Seam(有焊接)
Plating: Tin(镀锡)




ITEM NO 型 号	USA Screw 美制螺栓号	Screw dia 螺栓口直径 d2(mm)	Dimension尺寸(mm)							WIPR RANGE AWG/mm ²	Plating
			W	L	F	E	D	d1	T		
SNB1.25-3	#4	3.2	5.7	16.0	6.5	4.8	3.4	1.7	0.75	22-16AWG 0.5-1.2mm ² 19A	
SNB1.25-3.5S	#6	3.7	5.7	16.0	6.5						
SNB1.25-3.5L	#6	3.7	6.4	16.0	6.5						
SNB1.25-4S	#6	4.3	6.4	16.0	6.5						
SNB1.25-4M	#8	4.3	7.2	16.0	6.5						
SNB1.25-4L	#8	4.3	8.1	16.0	6.5						
SNB1.25-5S	#10	5.3	8.1	16.0	6.5						
SNB1.25-5L	#10	5.3	9.5	16.0	6.5	4.8	4.1	2.3	0.8	16-14AWG 1.5-2.5mm ² 27A	
SNB1.25-6S	1/4	6.4	9.5	16.0	6.5						
SNB1.25-6L	1/4	8.4	12.0	22.0	11.0						
SNB2-3	#4	3.2	5.7	16.0	6.5						
SNB2-3.5S	#6	3.7	5.7	16.0	6.5						
SNB2-3.5L	#6	3.7	6.0	16.0	6.5						
SNB2-4S	#6	4.3	6.4	16.0	6.5						
SNB2-4M	#8	4.3	7.2	16.0	6.5						
SNB2-4L	#8	4.3	8.1	16.0	6.5						
SNB2-5S	#10	5.3	8.1	16.0	6.5	6.0	5.0	3.0	1.0	14-12AWG 2.5-4mm ² 37A	
SNB2-5L	#10	5.3	9.5	16.0	6.5						
SNB2-6S	1/4	6.4	9.5	16.0	6.5						
SNB2-6L	1/4	6.4	12.0	22.0	11.0	6.8	5.6	3.4	1.0	12-10AWG 4-6mm ² 48A	
SNB3.5-4	#8	3.2	5.7	18.3	7.0						
SNB3.5-5S	#10	4.3	8.0	18.3	7.0						
SNB3.5-5L	#10	5.3	8.0	18.3	7.0	8.5	7.2	4.5	1.2	8AWG 8mm ² 115A	
SNB3.5-6	1/4	6.4	12.0	21.5	12.1						
SNB5.5-3.5	#6	3.7	8.3	19.5	7.5						
SNB5.5-4S	#8	4.3	8.3	19.5	7.5	10.5	9.0	5.8	1.7		
SNB5.5-4L	#8	4.3	9.0	19.5	7.5						
SNB5.5-5	#10	5.3	9.0	19.5	7.5						
SNB5.5-6S	1/4	6.4	9.0	19.5	7.5	12.0	12.0	11.5			
SNB5.5-6L	1/4	6.4	12.0	25.5	12.0						
SNB5.5-8	5/16	8.4	14.0	24.5	11.5						
SNB8-4	#8	4.3	8.7	23.0	6.0	8.5	7.2	4.5	1.4		
SNB8-5	#10	5.3	12.0	24.5	5.7	8.5	7.2	4.5			
SNB8-6	1/4	6.4	12.0	24.5	5.7	8.5	7.2	4.5			
SNB8-8	5/16	8.4	14.5	28.0	8.3	8.5	7.2	4.5	1.7		
SNB14-6	1/4	6.4	12.0	28.0	7.5	10.5	9.0	5.8			
SNB14-8	5/16	8.4	14.0	28.0	7.5	10.5	9.0	5.8			
SNB22-8	5/16	8.4	14.0	34.5	9.0	12.0	12.0	11.5			

裸中间接管 Non-insulatde Butt Connector



Terminal Material:copper(紫铜)
Brezed Sean(有焊接)
Plating:Tin(镀锡)




ITEM NO 型 号	Cable size 电缆规格		Dimension尺寸(mm)			Plating
	A.W.G	mm ²	D	d	L	
BN 1.25	22-16	0.5-1.5	3.3	1.7	15.0	Tin
BN 2	16-14	1.5-2.5	4.0	2.3	15.0	
BN 3.5	14-12	2.5-4	5.0	3.0	15.0	
BN 5.5	12-10	4-6	5.5	3.4	15.0	
BN 8	#8	10	7.1	4.5	21.0	
BN 14	#6	16	9.0	5.8	26.0	
BN 22	#4	25	11.4	7.7	29.0	
BN 38	#2	35	13.3	9.4	32.0	
BN 60	1/0	50	15.4	11.4	36.0	
BN 70	2/0	70	17.5	13.3	37.0	
BN 80	3/0	95	19.4	14.5	38.0	
BN 100	4/0	120	22.0	16.4	38.0	



适用于标称截面1.5~100mm²电力电缆式电线的铜导体与电气设备的连接，特点，采用管料含铜量>99.9%的高纯T2管制造，长期工作温度-55℃~150℃，表面镀锡。

These products are suitable for the connection of copper conductors (section 1.5~100mm²) in power cable with electronic equipment they are made of with higher 99.9percent pure copper tube T2 and coated with tin working temperature -55℃~150℃.



材质：紫铜管 Material: Copper

ITEM NO 型 号	Screw dia. 螺栓口直径d2Φ(mm)		Dimension尺寸(mm)						Cable size 导线截面(mm ²)
	W	Φd	D	L	L1	S			
SC1.5-5	#10	5.3	8	1.8	3.3	16	-	-	1.5
SC2.5-4	#8	4.3	8	2.4	4	19.6	8	-	2.5
SC2.5-5	#10	5.3	8	2.4	4	19.6	8	-	2.5
SC2.5-6	1/4	6.5	10	2.4	4	21	8	-	2.5
SC4-4	#8	4.3	10	3.1	4.8	21	-	-	4
SC4-5	#10	5.3	10	3.1	4.8	21	-	-	4
SC4-6	1/4	6.5	10	3.1	4.8	21	-	-	4
SC6-4	#8	4.3	10	3.8	5.5	25.5	-	-	6
SC6-5	#10	5.3	10	3.8	5.5	25.5	-	-	6
SC6-6	1/4	6.5	10	3.8	5.5	25.5	-	-	6
SC10-6	1/4	6.5	12.6	4.5	6.2	27	10	1.1	10
SC10-8	5/16	8.4	12.6	4.5	6.2	27	10	1.1	10
SC16-6	1/4	6.5	12.6	5.5	7.2	29.5	10.5	1.3	16
SC16-8	5/16	8.4	12.6	5.5	7.2	29.5	10.5	1.3	16
SC25-6	1/4	6.5	15	7	9	33	12	1.65	25
SC25-8	5/16	8.4	15	7	9	33	12	1.65	25
SC25-10	3/8	10.5	15	7	9	33	12	1.65	25
SC35-6	1/4	6.5	15.2	8.2	10.6	38	14.2	2.5	35
SC35-8	5/16	8.4	15.2	8.2	10.6	38	14.2	2.5	35
SC35-10	3/8	10.5	15.2	8.2	10.6	38	14.2	2.5	35
SC50-8	5/16	8.4	18.5	10	13	44.5	18	2.9	50
SC50-10	3/8	10.5	18.5	10	13	44.5	18	2.9	50
SC50-12	1/2	13	18.5	10	13	44.5	18	2.9	50
SC70-8	5/16	8.4	21.4	11.5	15	54.2	20.4	3.5	70
SC70-10	3/8	10.5	21.4	11.5	15	54.2	20.4	3.5	70
SC70-12	1/2	13	21.4	11.5	15	54.2	20.4	3.5	70
SC95-10	3/8	10.5	25.5	13.5	17.4	59	23.4	3.9	95
SC95-12	1/8	13	25.5	13.5	17.4	59	23.4	3.9	95
SC120-10	3/8	10.5	28.3	15.5	19.9	66.7	24.6	4.5	120
SC120-12	1/2	13	28.3	15.5	19.9	66.7	24.6	4.5	120
SC120-14	9/16	15	28.3	15.5	19.9	66.7	24.6	4.5	120
SC120-16	5/8	17	28.3	15.5	19.9	66.7	24.6	4.5	120
SC150-12	1/2	13	31	17	21.7	74.5	29.5	4.5	150

Packaging & Shipping

Terminal Value Of Packaging



Value Pack: N-175(plastic box)
175 PCS 18 TYPE Assortment

ITEM NO.	数量 QTY	ITEM NO.	数量 QTY	ITEM NO.	数量 QTY
RV1.25-3	15	RV5.5-5	5	BV2	10
RV5.1.25-4	10	RV5.5-6	5	BV5.5	5
RV1.25-5	10	SV1.25-3	10	MD01.25-250	10
RV2-3	15	SV5.1.25-4	10	MD02-250	10
RV52-4	10	SVL2-4	10	FDD1.25-250	10
RVL2-5	10	BV1.25	10	FDD2-250	10



Value Pack: N-175(plastic box)
175 PCS 18 TYPE Assortment

ITEM NO.	数量 QTY	ITEM NO.	数量 QTY	ITEM NO.	数量 QTY
RV1.25-3	25	RV5.5-5	5	Bx2	10
RV5.1.25-4	25	RV5.5-6	5	BV5.5	5
RV1.25-5	25	SV1.25-3	20	MD01.25-250	20
RV2-3	15	SV5.1.25-4	20	MD02-250	20
RV52-4	20	SVL2-4	20	FDD1.25-250	20
RVL2-5	10	BV1.25	10	FDD2-250	20

Packaging Details:

Customized Packing: Header card packing, Blister with card packing, Double blister packing, Canister packing, other packing can be supplied according customers request.

Shipping:

1. By Air or by Sea for batch goods,Airport/ Port receiving;

2. Customers specifying freight forwarders or negotiable shipping methods!

Delivery Detail:

Shipped in 7 days after payment

Company Profile

- Golden Electric Co.,Ltd ,was foundad in 2017, we are professional for makeAC and DC electric items such as cable gland,cable tie ,isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

Recommend Products



Closed end Terminal



Nylon Connectors



Tube Type Terminal



Plug-in Terminal



Copper Bare Terminal



Insulated Copper Terminals

Our Advantages

- 1.Best ensure 100% customer satisfaction.
- 2.Our products have one year guarantee.
- 3.Sample in design and easy to operate and maintain.
- 4.All electrical parts of products are made up for qualified marterials.
- 5.No MOQ limited for the trial order.
- 6.We adopt good credit quality electrial appliances.
- 7.Best customer care and efficient after-sale services.
- 8.Don't hesitate to inquire us,we will reply you within 12 hours.

Production and transport



FAQ

Q1: Could I Put My Own Logo On It?

A1: Sure, of course, we are a professional manufacturer and have over 10 years OEM experience, customer;s logo can be made by laser, engraved, embossed, transfer printing etc.

Q2: What's the delivery time?

A2: Normally, 3-15days after order and payment confirmation. Actually, it will depend on your orderquality.

Q3: What's your terms of payment?

A3: T/T 30% as deposit, and 70% before delivery. We'll show you the photos of the products and packages before you pay the balance.

Q4: How do you make our business long-term and good relationship?

A4: a. We keep good quality and competitice price to ensure our customers benefit; b. We respect every customer as our friend and we sincerely do business and make friends with them, no matter where they come from.

Q5: If we bought your products, but found quality problem, how to solve?

A5: After confirmed, if the quality problem is caused by us not for outer sector, we will compensate each piece to customer.

How to contact us

Send your Inquiry Details in the Below, please Click "[send](#)" Now!
Good price and sample are waiting for you.



Guangzhou Golden Electric Co., Ltd.



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,
Guangzhou city,Guangdong province,China