



## Nylon 66 Cable Tie Strap Plastic Tie Selflocking UL UV Protected PA66 Material

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months  
Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month



### Product Specification

- OEM: Accept
- Feature: Flamme-Retardant, Heat-Resistant
- Working Temperature: -40c-85c
- Packing: 100PCS/Bag 250PCS/Bag
- Sample: Provide
- Tensile Strength: 8-175kgs
- Operating Temperature: -30c To 85c
- Bundle Diameter(mm): 3-65
- Product Name: Nylon Cable Ties Self-Locking
- Transport Package: Blank Poly Bag + Neutral Label + Export Carton
- Specification: Length 80mm-1220mm Width 1.8mm-9mm
- Trademark: Golden Or Natural Or Customer Brand
- Origin: China
- HS Code: 3926909090



### More Images



for more products please visit us on [chinagoldene.com](http://chinagoldene.com)

## Product Description

Product Description	
Material:	Nylon66(ULapproved material)
Structure:	Self locking head
Color:	White/black/nature standard color, other colors are available on request
Working temperature:	Applied from -40°C to 85°C
Length:	All lengths are available
Feature:	Flame-retardant(94V-2), heat-resistant
Certificate:	RoHS, CE
Usage:	First, the cable is bundled in the nylon cable tie;
	Next,the tail of the nylon cable tie is clamped by the tool;
	Finally, tighten with tool
Application:	Used to bundle cables, wires, conducts, plants or other things in the industry of electrical & electronic, lighting, hardware, pharmaceutical, chemical, computer, machinery, agriculture, etc.
Delivery time:	7-15 days (Depend on your order quantity) after confirm order.
Payment terms:	T/T,Western Union,L/C ,PayPal



### Feature:

- 1.Eco-friendly.
- 2.Non-slips design, strong fixed
- 3.Good tensile strength and insulation.
- 4.Acids and alkali resistant.
- 5.Good toughness, not easy to break
- 6.Not easy to get aging.

### Application:

#### Use and scene display



### Best selling



## Product Parameters

Item No.	Bundle diameter(mm)	Width(mm)	Length(mm) Min.loop tensile strength			
			INCH	MM	KGS	LBS
GD-3*80	(2-16)	2.5	3.2"	80	8	18
GD-3*100	(2-22)	2.5	4"	100	8	18
GD-3*120	(2-30)	2.5	4.7"	120	8	18
GD-3*150	(2-35)	2.5	6"	150	8	18
GD-3*200	(3-50)	2.5	8"	200	8	18
GD-4*150	(3-35)	3.6	6"	150	18	40
GD-4*180	(3-42)	3.6	7.1"	180	18	40
GD-4*200	(3-50)	3.6	8"	200	18	40
GD-4*250	(3-65)	3.6	10"	250	18	40
GD-4*300	(3-80)	3.6	12"	300	18	40
GD-4*350	(3-90)	3.6	14"	350	18	40
GD-4*370	(3-102)	3.6	14.6"	370	18	40
GD-4*400	(3-105)	3.6	16"	400	18	40
GDA-5*150	(3-35)	4.6	6"	150	22	50
GDA-5*180	(3-42)	4.6	7.1"	180	22	50
GDA-5*200	(3-50)	4.6	8"	200	22	50
GDA-5*250	(3-65)	4.6	10"	250	22	50
GDA-5*300	(3-82)	4.6	12"	300	22	50
GDA-5*350	(3-90)	4.6	14"	350	22	50
GDA-5*380	(3-102)	4.6	15"	380	22	50
GDA-5*400	(3-105)	4.6	16"	400	22	50
GD-5*150	(3-35)	4.8	6"	150	22	50
GD-5*180	(3-42)	4.8	7.1"	180	22	50
GD-5*200	(3-50)	4.8	8"	200	22	50
GD-5*250	(3-65)	4.8	10"	250	22	50
GD-5*300	(3-82)	4.8	12"	300	22	50
GD-5*350	(3-90)	4.8	14"	350	22	50
GD-5*380	(3-102)	4.8	15"	380	22	50
GD-5*400	(3-105)	4.8	16"	400	22	50
GD-5*450	(3-130)	4.8	18"	450	22	50
GD-5*500	(3-150)	4.8	20"	500	22	50
GD-8*200	(3-50)	6.8	8"	200	55	120
GD-8*250	(4-60)	7.6	10"	250	55	120
GD-8*300	(4-80)	7.6	12"	300	55	120
GD-8*350	(4-88)	7.6	14"	350	55	120
GD-8*380	(4-98)	7.6	15"	380	55	120
GD-8*400	(4-105)	7.6	16"	400	55	120
GD-8*450	(4-116)	7.6	18"	450	55	120
GD-8*500	(4-148)	7.6	20"	500	55	120
GD-8*550	(4-150)	7.6	22"	550	55	120
GD-9*400	(8-110)	8.7	16"	400	80	175
GD-9*450	(8-115)	8.7	18"	450	80	175
GD-9*500	(8-150)	8.7	20"	500	80	175
GD-9*550	(8-160)	8.7	22"	550	80	175
GD-9*600	(8-180)	8.7	24"	600	80	175
GD-9*650	(8-190)	8.7	25.6"	650	80	175
GD-9*720	(10-208)	8.7	28.3"	720	80	175
GD-9*760	(10-223)	8.7	29.9"	760	80	175
GD-9*800	(10-230)	8.7	31.5"	800	80	175

GD-9*850	(10-235)	8.7	33.5"	850	80	175
GD-9*920	(10-265)	8.7	35.4"	920	80	175
GD-9*1020	(10-290)	8.7	40"	1020	80	175
GD-9*1220	(10-340)	8.7	40.2"	1220	80	175

## Packaging & Shipping

### Packing:

For Free : Design new sticker label with your own LOGO

Popular packing :

100 pcs/pkt + PE Polybag + Adhesive sticker + export carton

**OEM service:**Support different customized packing

### Shipping:

1. By Air or by Sea for batch goods,Airport/ Port receiving;
2. Customers specifying freight forwarders or negotiable shipping methods!

### Delivery Detail:

Shipped in 7 days after payment



## Company Profile

- Golden Electric Co.,Ltd ,was founded in 2017, we are professional for make **AC and DC electric items such as cable gland,cable tie ,isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product** and so on.

- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.

- Golden is always striving hard to provide the best services and competitive price to all customers.

## Recommend Products



view it



view it



view it



view it



view it



view it



view it



view it



view it

#### Our Advantages

1. Best ensure 100% customer satisfaction.
2. Our products have one year guarantee.
3. Sample in design and easy to operate and maintain.
4. All electrical parts of products are made up for qualified materials.
5. No MOQ limited for the trial order.
6. We adopt good credit quality electrical appliances.
7. Best customer care and efficient after-sale services.
8. Don't hesitate to inquire us, we will reply you within 12 hours.

#### Production and transport



#### FAQ

**Q1: Could I Put My Own Logo On It?**

A1: Sure, of course, we are a professional manufacturer and have over 10 years OEM experience, customer's logo can be made by laser, engraved, embossed, transfer printing etc.

**Q2: What's the delivery time?**

A2: Normally, 3-15 days after order and payment confirmation. Actually, it will depend on your order quality.

**Q3: What's your terms of payment?**

A3: T/T 30% as deposit, and 70% before delivery. We'll show you the photos of the products and packages before you pay the balance.

**Q4: How do you make our business long-term and good relationship?**

A4: a. We keep good quality and competitive price to ensure our customers benefit; b. We respect every customer as our friend and we sincerely do business and make friends with them, no matter where they come from.

**Q5: If we bought your products, but found quality problem, how to solve?**

A5: After confirmed, if the quality problem is caused by us not for outer sector, we will compensate each piece to customer.

## **How to contact us**

**Send your Inquiry Details in the Below, please Click "[send](#)" Now!**

**Good price and sample are waiting for you.**



**Guangzhou Golden Electric Co., Ltd.**



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,  
Guangzhou city, Guangdong province, China