

BV Copper Insulated Middle Cable Connector Terminal with Sample Acceptance from Buyers

Basic Information

Place of Origin: China

Brand Name: Golden Electric /OEM

• Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000,

ISO 20000, OHSAS/ OHSMS 18001,

IATF16949

Minimum Order Quantity:

• Packaging Details: Carton/Pallet

Delivery Time: Peak Season Lead Time: more than 12

months Off Season Lead Time: within 15

workdays

• Payment Terms: LC, T/T, PayPal, Western Union

Supply Ability: 5000/Month



Product Specification

Shape: TubularInterface Type: AC/DC

• Brand: Golden Electric/OEM

• Rated Voltage: 415V

Entry: Chamfered Entry
Busbar: -55c~150c
Size: 1.5~600mm2

Coating: TinOEM: AcceptSample: Accept

• Wire Range: 22~16/16~14/14~12/12~10 A.W.G

• Color: Natural

Product Key Words: Insulated Terminal Blocks

Imax: 27AShell Material: PVC



More Images









Product Description



Product Details:

- 1. The SC series copper cable lugs are suitable for the connection of copper conductors(section 1.5-1000mm2)in power cable with electronic equiqment.
- 2. the cable lugs are made of with higher 99.9 percent pute copper tube T2 and coated with tin.
- 3. Working temperature-55°C-150°C.


Product Parameters

Insulated Female Disconnector



Terminal Material: Brass Plating: electro Tin Plated Insulation Material: vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC




ITEM NO	NAME TAB(mm)	Thickness of material		DIMEN	SIONS	(mm)[产		WIRE RANGE	Color
型 号	NAME IAD(IIIII)	I nickness of material	W	D	С	L	В	AWG/mm ²	颜色
FDD 1.25-110(5)	0.5×2.8	0.3	3.8	3.8	1.7	19.0	10.0		
FDD 1.25-110(8)	0.8×2.8	0.3	3.8	3.8	1.7	19.0	10.0		
FDD 1.25-187(5)	0.5×4.75	0.35	5.6	3.8	1.7	19.0	10.0	22~16AWG	Redi
FDD 1.25-187(8)	0.8×4.75	0.35	5.6	3.8	1.7	19.0	10.0	0.5~1.5/mm²	
FDD 1.25-205	0.5×5.2	0.35	6.5	3.8	1.7	20.0	10.0	10A	
FDD 1.25-250	0.8×6.35	0.4	7.4	3.8	1.7	21.0	10.0		
FDD 2-110(5)	0.5×2.8	0.3	3.8	4.3	2.3	19.0	10.0		
FDD 2-110(8)	0.8×2.8	0.3	3.8	4.3	2.3	19.0	10.0		
FDD 2-187(5)	0.5×4.75	0.35	5.6	4.3	2.3	19.0	10.0		
FDD 2-187(8)	0.8×4.75	0.35	5.6	4.3	2.3	19.0	10.0	16~14AWG 1.5~2.5/mm ²	Blue 蓝
FDD 2-205	0.5×5.2	0.35	6.5	4.3	2.3	20.0	10.0	15A	
FDD 2-250	0.8×6.35	0.4	7.4	4.3	2.3	21.0	10.0		
FDD 2-312	0.8×8.0	0.4	9.0	4.3	2.3	23.0	10.0		
FDD 5.5-187	0.5×4.75	0.4	5.6	5.7	3.4	23.0	14.0		
FDD 5.5-250	0.8×6.35	0.4	7.4	5.7	3.4	25.0	13.0	12-10AWG	Yellow #
FDD 5.5-312	0.8×8.0	0.5	9.0	5.7	3.4	27.0	14.0	4~6/mm² 24A	
FDD 5.5-375	1.2×9.4	0.5	10.9	5.7	3.4	29.6	13.0	246	

Insulated Male Disconnector



Terminal Material:Brass Plating:electro Tin Plated Insulation Material:vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC




Color	WIRE RANGE		(mm)	nsion尺寸	Dime		Thickness of material	NAME TAB(mm)	ITEM NO
颜色	AWG/mm ²	В	L	С	D	W	I nickness of material	NAME IAD(IIIII)	코 등
		10.0	17.7	4.3	1.7	2.8	0.5	0.5×2.8	MDD 1.25-110(5)
		10.0	17.7	4.3	1.7	2.8	0.8	0.8×2.8	MDD 1.25-110(8)
Red 红	22~16AWG	10.0	20.0	4.3	1.7	4.75	0.5	0.5×4.75	MDD 1.25-187(5)
•	0.5~1.5/mm ²	10.0	20.0	4.3	1.7	4.75	0.8	0.8×4.75	MDD 1.25-187(8)
	10A	10.0	21.0	4.3	1.7	6.35	0.4×2	0.8×6.35	MDD 1.25-250
		10.0	17.7	4.3	2.3	2.8	0.5	0.5×2.8	MDD 2-110(5)
	100000000000000000000000000000000000000	10.0	17.7	4.3	2.3	2.8	0.8	0.8×2.8	MDD 2-110(8)
Blue 蓝	16~14AWG 1.5~2.5/mm ²	10.0	20.0	4.3	2.3	4.75	0.5	0.5×4.75	MDD 2-187(5)
	15A	10.0	20.0	4.3	2.3	4.75	0.8	0.8×4.75	MDD 2-187(8)
		10.0	21.0	4.3	2.3	6.35	0.4×2	0.8×6.35	MDD 2-250
Yellow 1	12~10AWG	13.0	23.0	5.7	3.4	4.75	0.5	0.5×4.75	MDD 5.5-187
	4~6/mm1 24A	13.0	25.0	5.7	3.4	6.35	0.4×2	0.8×6.35	MDD 5.5-250

Full Insulated Female Disconnector



Terminal Material: Brass Plating: electro Tin Plated Insulation Material: vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC




ITEM NO	NAME TAB(mm)	This have a factorial		Dime	nsion尺寸	(mm)		WIRE RANGE	Color
코 등	NAME IAB(IIIII)	Thickness of material	W	D	С	L	В	AWG/mm ²	颜色
MDD 1.25-110(5)	0.5×2.8	0.5	2.8	1.7	4.3	17.7	10.0		
MDD 1.25-110(8)	0.8×2.8	0.8	2.8	1.7	4.3	17.7	10.0		
MDD 1.25-187(5)	0.5×4.75	0.5	4.75	1.7	4.3	20.0	10.0	22~16AWG	Red红
MDD 1.25-187(8)	0.8×4.75	0.8	4.75	1.7	4.3	20.0	10.0	0.5~1.5/mm ²	•
MDD 1.25-250	0.8×6.35	0.4×2	6.35	1.7	4.3	21.0	10.0	10A	
MDD 2-110(5)	0.5×2.8	0.5	2.8	2.3	4.3	17.7	10.0		
MDD 2-110(8)	0.8×2.8	0.8	2.8	2.3	4.3	17.7	10.0		
MDD 2-187(5)	0.5×4.75	0.5	4.75	2.3	4.3	20.0	10.0	16~14AWG 1.5~2.5/mm ²	Blue 蓝
MDD 2-187(8)	0.8×4.75	0.8	4.75	2.3	4.3	20.0	10.0	15A	
MDD 2-250	0.8×6.35	0.4×2	6.35	2.3	4.3	21.0	10.0		
MDD 5.5-187	0.5×4.75	0.5	4.75	3.4	5.7	23.0	13.0	12~10AWG	Yellow 1
MDD 5.5-250	0.8×6.35	0.4×2	6.35	3.4	5.7	25.0	13.0	4~6/mm1 24A	1,000,000

Insulated Bullet Disconnector



Terminal Material:Brass Plating:electro Tin Plated Insulation Material:vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC




ITEM NO	Nema Tab		Dimensio	n尺寸(mm)		WIRE RANGE	Color 颜色
型 号	(mm)	В	DΦ	dΦ	L	AWG/mm ²	颜色
FDFD 1.25-187(5)	0.5×4.75	5.6	3.8	1.7	20.0	***************************************	
FDFD 1.25-187(8)	0.8×4.75	5.6	3.8	1.7	20.0	22~16AWG 0.5~1.5/mm²	Red 红
FDFD 1.25-250	0.8×6.35	7.4	3.8	1.7	21.5	10A	
FDFD 2-187(5)	0.5×4.75	5.6	4.3	2.3	20.0		
FDFD 2-187(8)	0.8×4.75	5.6	4.3	2.3	20.0	16~14AWG 1.5~2.5/mm ²	Blue 蓝
FDFD 2-250	0.8×6.35	7.4	4.3	2.3	21.5	15A	
FDFD 5.5-250	0.8×6.35	7.4	5.7	3.4	25.5	12~10AWG 4~6/mm ² 24A	Yellow #

Full Insulated Receptacle Disconnector



Terminal Material:Brass Plating:electro Tin Plated Insulation Material:vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC




ITEM NO	Thickness of material			Dimension	n尺寸(mm)			WIRE RANGE	Color 颜色
型号	i nickness of material	W	F	С	В	L	D	AWG/mm²	颜色
FRD 1.25-156	0.4	4.0	6.3	1.7	13.0	24.5	2.7	22~16AWG 0.5~1.5/mm ² 10A	Red 红
FRD 2-156	0.4	4.0	6.3	2.3	14.0	24.5	3.3	16~14AWG	Blue 蓝
FRD 2-195	0.4	5.0	7.0	2.3	14.0	25.5	3.3	1.5~2.5/mm² 15A	•
FRD 5.5-195	0.4	5.0	7.0	3.4	14.0	29.5	4.5	12-10AWG 4~6/mm2 24A	Yellow 3

Insulated Piggy Back Disconnector



Terminal Material:Brass Plating:electro Tin Plated Insulation Material:vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC




ITEM NO	NAMA TAB			Dimension	尺寸(mm)			WIRE	Color 颜色
型号	NAMA IAD	В	B1	Н	Dφ	dφ	L	AWG/mm²	颜色
PBDD 1.25-250	0.8 × 6.35	7.4	6.35	10.0	3.8	1.7	21.5	22~16AWG 0.5~1.5/mm ² 10A	Red 红
PBDD 2-250	0.8 × 6.35	7.4	6.35	10.0	4.3	2.3	21.5	16~14AWG 1.5~2.5/mm ³ 15A	Blue 蓝
PBDD 5.5-250	0.8×635	7.4	6.35	13.0	5.7	3.4	25.0	12~10AWG 4~6/mm2 24A	Yellow 黄

Nylon Insulated Flag Female Disconnector



Terminal Material: Brass Plating: electro Tin Plated Insulation Material: vinyl(pvc)

端子材料: 黄铜 电镀: 铜锡 绝缘材料: PVC



ITEM NO	Nema Tab		Dimensio	n尺寸(mm)		WIRE	Color
型 号	(mm)	W	F	L	dΦ	AWG/mm ²	Color 颜色
FLDNY 1 25-250	0.8×6.35	6.6	7.6	16.0	1.7	22~16AWG 0.5~1.5/mm² 10A	Red 红
FLDNY 2-250	0.8×6.35	6.6	7.6	16.0	2.3	16~14AWG 1.5~2.5/mm² 15A	Blue 蓝
FLDNY 5.5-250	0.8×6.35	6.6	7.6	16.0	3.4	12-10AWG 4-6/mm2 24A	Yellow 賞

Quick Splice Connector



Terminal Material:Copper Plating:electro Tin Plated Insulation Material: Nylon

端子材料: 紫铜 电镀: 铜锡 绝缘材料: 尼龙




ITEM NO	Dimension	n尺寸(mm)	Cable size	他都两/mm²\	Color颜色
로 号	W	L	Cable sizely	az az antum.	COIOTINE
878100	20.0	27.0	22-18A.W.G	0.5-1.0mm2	● Red 红色
878101	20.0	27.0	18-14A.W.G	0.75-2.5mm2	● Bule 蓝色
878101	20.0	27.0	18-14A.W.G	0.72-2.5mm2	〇 White 白色
878201	20.5	34.5	12-10A.W.G	4-6mm2	O Yellow 黄色

Quick Splice Connector



Terminal Material: Copper Plating: electro Tin Plated Insulation Material: Nylon

端子材料 紫铜 电镀:铜锡 绝缘材料 尼龙



ITEM NO	DIMENSION	I尺寸(mm)	WIRE RANGE	Color
型 号	W	L	AWG/mm ²	0000
Т1	9.8	37.0	22-18AWG 0.5~0.75mm ^a	Red
T2	9.8	37.0	18~14AWG 0.75~2.5mm ²	Blue
тз	9.8	37.0	12AWG 4mm'	Yellow

Packaging & Shipping

Terminal Value Of Packaging





IR 9 ITEMANS.	019 011	ITEM NO.	818 019	ITEM NO.	8/8 (211
P(1.25/A	16	81550		842	11
PV01264	26	8/554	*	PIST	
PH1200		99126-0	26	MEDICAL	
MES	16	5151264	20	M000-290	19
MISS-R	30	0534	in .	FD0126280	20
MISS .	10	891.05	16	F000 area	20

Packaging Details:

Customized Packing: Header card packing, Blister with card packing, Double blister packing, Canister packing, other

packing can be supplied according customers request.

Shipping:

- 1. By Air or by Sea for batch goods, Airport/ Port receiving;
- 2. Customers specifying freight forwarders or negotiable shipping methods!

Delivery Detail:

Shipped in 7 days after payment

Company Profile

- Golden Electric Co.,Ltd ,was founded in 2017, we are professional for makeAC and DC electric items such as cable gland,cable tie ,isolator switch , fuse , breaker , distribution box , PV combiner box ,surge protector, Industrial plug and socket,Solar product and so on.
- Golden has been granted ISO9001 management system certifications. The comprehensive product line has more than 1000 models which have been approved by TUV,CE,CQC,SGS,ROHS,SASO. The productsells well to UK, Spain, Portugal, Singapore, Turkey, Russia, Korea, South Africa... more than 60 countries and regions.
 - Golden is always striving hard to provide the best services and competitive price to all customers.

Recommend Products



Closed end Terminal



Nylon Connectors



Tube Type Terminal



Plug-in Terminal



Copper Bare Terminal



Insulated Copper Terminals

Our Advantages

- 1.Best ensure 100% customer satisfaction.
- 2. Our products have one year guarantee.
- 3. Sample in design and easy to operate and maintain.
- 4.All electrical parts of products are made up for qualitified marterials.
- 5.No MOQ limited for the trial order.
- 6. We adopt good credit quality electrial appliances.
- 7.Best customer care and effcient after-sale services.
- 8.Don't hesitate to inquire us, we will reply you within 12 hours.

Q1: Could I Put My Own Logo On It?

A1: Sure, of course, we are a professional manufacturer and have over 10 years OEM experience, customer;s logo can be made by laser, engraved, embossed, transfer printing etc.

Q2: What's the delivery time?

A2: Normally, 3-15days after order and payment confirmation. Actually, it will depend on your orderquality.

Q3: What's your terms of payment?

A3: T/T 30% as deposit, and 70% before delivery. We'll show you the photos of the products and packages before you pay the balance.

Q4: How do you make our business long-term and good relationship?

A4: a. We keep good quality and competitice price to ensure our customers benefit; b. We respect every customer as our friend and we sincerely do business and make friends with them, no matter where they come from.

Q5: If we bought your products, but found quality problem, how to solve?

A5: After confirmed, if the quality problem is caused by us not for outer sector, we will compensate each piece to customer.

How to contact us

Send your Inquiry Details in the Below, please Click "send" Now! Good price and sample are waiting for you.



Guangzhou Golden Electric Co., Ltd.



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District, Guangzhou city, Guangdong province, China