

Insulated Terminal Ring Copper Connectors for Crimping Auto Electrical Wires 2-22 AWG

Basic Information

- Place of Origin:
- Brand Name: Golden Electric /OEM ISO 9001, ISO 9000, ISO 14001, ISO 14000, Certification: ISO 20000, OHSAS/ OHSMS 18001, IATF16949 RV1.25series Model Number: • Minimum Order Quantity: 1 Packaging Details: Carton/Pallet • Delivery Time: Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15 workdays

China

- LC, T/T, PayPal, Western Union • Payment Terms: 5000/Month
- Supply Ability:



Product Specification

• Wire Range:	2-22 AWG
Color:	Red Blue Black Yellow
• Plating:	Tinned
• Style:	Ring Terminal
 Insulation Material: 	PVC/Nylon 66/Heat Shrink Tube
• Feature:	Fireproof/Moisture-Proof/High Conductivity
• Sample:	Free
• MOQ:	1 Bag
• OEM:	Accept
 Transport Package: 	Ocean Freight Air Freight
 Specification: 	Different Sizes And Specifications
• Trademark:	Golden Electric Or Customize
• Origin:	China
• HS Code:	8538900000
 Supply Ability: 	5000/Month



More Images









Our Product Introduction

Product Description

Company Profile

GoldenElectricCo., Ltd.

is professional make of Electrical products .Such as distribution box, waterproof plug, socket, wall switch, waterproof plastic ,Aluminum box ,Changeover Switch and disconnecting switch,MC4 Connector.isolator switch.fusebreaker.distribution box,PV combiner box .surge protector, Indicatorlamp,Solar Charge Controller,Industrialplugandsocket,BusbarInsulator,Meter Socket,Wind Turbine, Terminal Block,Solar product and so on. all products comply with IEC, A S/NZS standard. passed CE, IP66, ROHS certificates.at present we have exported to many countries and have serve these customers with professional electrical solution.

Product Description

Terminal material	Brass or copper				
Sheath material	PVC/Nylon PA66/Double wall heat shrinkable tubing				
Surface treatment	Tinned (Or according to customer requirements)				
A.W.G	2-22 AWG				
Operating temperature	-45°C-125°C				
Maximum current	19A-160A				
Color	Red/Yellow/Blue/Black	(Accept customization)			












Conductor section: 0.5-1.5m (A.W.G 22-16) Maximum current: IMAX=19A

Itom NO	Dimension(mm)								
Item NO	USA screw	Screw dia. d2	В	L	F	н	Dφ	т	Color
RV1.25-3	#4	3.2	5.7	17.8	4.95				
RVS1.25-3.5	#6	3.7	5.7	17.8	4.95				
RVM1.25-3.5	#6	3.7	6.6	20.1	6.3				

RVL1.25-3.5	#6	3.7	8.0	21.5	7.0				
RVS1.25-4	#8	4.3	6.6	20.1	6.3				
RVL1.25-4	#8	4.3	8.0	21.5	7.0	10.0	4.3	0.75	Red
RV1.25-5	#10	5.3	8.0	21.5	7.0	10.0	4.3	0.75	neu
RV1.25-6	1/4	6.5	11.6	27.5	11.1				
RV1.25-8	5/16	8.4	11.6	27.5	11.1				
RV1.25-10	3/8	10.5	13.6	31.6	13.9				



Products Category



Solar PV Cable with MC4 Connector

MC4 Solar Crimping Tool Kits

FAQ	
-----	--

Q1: Are yo	u a factory	or trading	company
------------	-------------	------------	---------

- A1: We are a factory, we can guarantee our price is first-hand, very cheap and competitive.
- Q2: How does your factory do regarding quality control?
- A2: All the products will be 100% checked before the shipment
- Q3: When can I get the price?
- A3:Usually we quote within 24 hours after we get your inquiry.
- Q4: How could I get a sample?

A4: if you can not buy our product in your local area, we will ship a sample to you. You will be charged a sample price plus all related shipping costs. Express delivery charge depends on the quantity of the samples. Q5: What is the price of shipping?

A5: Depending upon the port of delivery, prices vary.

Any more query please contact with us, thank you!

