




Professional Lightning Protection System with Different Sizes and Specifications

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Golden Electric /OEM
- Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949
- Minimum Order Quantity: 1
- Packaging Details: Carton/Pallet
- Delivery Time: Peak Season Lead Time: more than 12 months
Off Season Lead Time: within 15 workdays
- Payment Terms: LC, T/T, PayPal, Western Union
- Supply Ability: 5000/Month



Product Specification

- Type: Ball Type
- OEM: Yes
- Categories: Lightning Rod
- Manufacturer: Yes
- Supplier By Country: China
- Transport Package: Oceanfreight Cartons+Wooden Cases+Pallet+Container
- Specification: Different Sizes And Specifications
- Trademark: Golden Electric Or Customize
- Origin: China
- HS Code: 8535400000
- Supply Ability: 5000/Month
- Structure: Tube Type Arrester
- Installation: Parallel Arrester
- Application: Lightning System, Lightning System



More Images



for more products please visit us on chinagoldene.com

Product Description

Product Description

Professional Lightning Protection System

Material	Copper or Brass or Copper Clad Steel or Stainless Steel
Service life	More than 50 Years
Characters	Characters
Available service mode	OEM,ODM
Certificate	ISO9001:2015

Negotiable Price According to different material/size and and Purchase quantity

Description Common Size(We accept customization)

Ball	Dia58mm
Base	100mmx100mmx3mm
Total Height	380mm

Rod Length	Rod diameter	Thread	Material
500mm	16mm	M16	Brass,copper
1000mm	16mm	M16	Brass,copper
1500mm	16mm	M16	Brass,copperl

Availa Dia:8mm-25mm; Length:300mm-2000mm

Base	Conductor size	Rod diamter	Material
1	50-95mm ² wire	16mm	Brass
2	25mmx3mm copper tape	16mm	Brass
Three Point Needle	Nos	Rod	Material
1	3	16mm	Brass,copper







Golden Electric



Application Scenarios



Earthing System






Golden Electric



Golden Electric







Lightning arrester is used for lightning system of power plant ,transformer station ,tower ,communication station ,airport,railway, subway station , high building ,computer room ,petro plant ,oil reservoir in the environmental of moist ,saline and alkaline ,acid and chemical corrosion medium environmental.

Installation

(A)The installation of lightning rod

Matters need attention during installation:

(1)The lightning rod and other metal part on the building should connected together;

(2)No low voltage cable or communication cable installed on the rod

(B)Installation of earthing tape and earthing grid

1. Installation of exposed earthing tape (grid) :Installed at the ridge ,eave(abat-vent) or edge of roof

(1)Installation at the concrete base of roof :The base can be made with the roof together ,and fixed to the roof.

(2) Installation on the parapet wall or gutter bracket

Installed along parapet wall and fixed with bracket ,and the bracket should be installed earlier .The working height of bracket

should be less than 150mm . The bracket for direct line should be first and then for the middle .The bracket should be 0.25-0.5m

away to the turning point if turning needed . The horizontal spacing of bracket is 1-1.5m ,and vertical interval is 1.5-2m and

even distribution

(3) Installation at ridge ,eave or edge of roof

Use concrete base or bracke

If make the base on site , please remove the corner of ridge tile first ,and make the bracket and ridge tile together;

The bracket should be 0.25-0.5m away to the turning point if turning needed . The horizontal spacing of bracket is 1-1.5m ,and

vertical interval is 1.5-2m and even distribution.

Packing & Delivery

Packaging Details Lightning Protection System packing: cartons+wooden cases+pallet+container

Lead time:

Quantity(pieces) 1 - 5051 - 1000 >1000

Lead time (days) 10 30 To be negotiated



Gty Type Naked Tube Butt Electric Crimp Copper Butt Connectors and Terminal



Surface Mounted Waterproof Industrial



Terminal Bolck Steel Mounting DIN Rails Switch



Surface Mounted Franch Type 2gang 1gan Socke Switch Socke

Waterproof

FAQ

1.Are you a trading company or manufacturer?
Manufacturer with factory!

2.What kinds of Grounding Material do you produce?
It covers grounding rod ,lightning rod ,connecting fixing ,conductor, exothermic welding kit, etc.

3.Is Customized Material available?
Yes, please offer your required specs.

4.Do you Accept OEM service?
YES!

5.What's your Delivery Time?
Normally 20-25days,please confirm with us before order!

6.What's the Payment Trems?
Usually,50% as deposit,50% before sending B/L by T/T.

7.How you pack products?

Normally, in steel pallet. We'll do according to customers' requirement.



Guangzhou Golden Electric Co., Ltd.



008618998498109



eva@china-golden.com.cn



chinagoldene.com

Building 4, Self-edited Building, No. 728, Kaichuang Avenue, Yunpu Industrial Zone, Huangpu District,
Guangzhou city,Guangdong province,China