

ISO Certified Copper Internal Threaded Grounding Rods for 13mm Diameter **Applications**

Basic Information

- Place of Origin:
- China Golden Electric /OEM Brand Name: Certification: ISO 9001, ISO 9000, ISO 14001, ISO 14000, ISO 20000, OHSAS/ OHSMS 18001, IATF16949 Model Number: Jdb-J047 • Minimum Order Quantity: 1 Packaging Details: Carton/Pallet • Delivery Time: Peak Season Lead Time: more than 12 months Off Season Lead Time: within 15
- Payment Terms:
- Supply Ability:



Product Specification

• Item:

- Material:
- Copper Layer Thickness:
- Purity Of Copper:
- Tensile Strength:
- Straightness Error:
- Service Life:
- Diameter:
- Length:
- Certication:
- Transport Package:
- Specification:
- Trademark:
- Origin:

Internal Threaded Grounding Rods

LC, T/T, PayPal, Western Union

Copper Layer And Steel Core >=0.254mm/0.5-1.0mm

>=99.95%

workdays

5000/Month

- >=580nm/mm
- <=1mm/M
- >=50 Years
- 12mm; 13mm; 13.5mm; 14mm
- 4FT; 6FT
- ISO9001: 2008
- Ocean Freight Woven Belt+Iron Pallet+Container
- **Different Sizes And Specifications**
- Golden Electric Or Customize
- China



More Images









for more products please visit us on chinagoldene.com

Our Product Introduction

Product Description

Company

Profile GoldenElectricCo., Ltd.

is professional make of Electrical products .Such as distribution box, waterproof plug, socket, wall switch, waterproof plastic ,Aluminum box ,Changeover Switch and disconnecting switch,MC4 Connector.isolator switch.fusebreaker.distribution box,PV combiner box .surge protector, Indicatorlamp,Solar Charge Controller, Industrial plugandsocket, BusbarInsulator, Meter Socket, Wind Turbine, Terminal Block, Solar product and so on. all products comply with IEC, A S/NZS standard. passed CE, IP66, ROHS certificates at present we have exported to many countries and have serve these customers with professional electrical solution.

Product Description

Item Material Copper Layer Thickness Straightness error Service life Tensile strength Purity of Copper Diameter Length Certificate

Internal Threaded Grounding Rods Copper Layer and Steel Core >=0.254mm/0.5-1.0mm <=1mm/m >=50 years >=580Nm/mm >=99.95% 12mm; 13mm; 13.5mm; 14mm 4ft; 6ft ISO9001: 2008









Products Details

Products Category

Internal Threaded Grounding Rods are widely used in power plants, substation, transmission line tower, communication base stations, airports, railways, all kinds of high-rise buildings, microwave relay station, the networkcomputer room, grounding, oil refinery, oil depots and other places to anti-static grounding, protective grounding, working, etc.

In recent years, accidents caused by grounding device faults increased day by day among enterprises of petroleum, electricity, communication and so on, so that great importance was attached to reliability, stability and service life of grounding devices. Therefore, electroforming copper cladding steel gradually substituted the traditional hot galvanized steel and hot fusion welding by right of its advantages of good conductivity performance, strong decay resistance, great tensile strength.

Copper Clad Stainless Steel Earth Rod				
Pure Copper Earth Rod				
	and the second s	-		
Material	Dia.(I	mm) Length	(ft) Weight(kg)	Remark
Copper Cald Stainless Steel	12	<u>2</u> 4ft	1.07	
Copper Cald Stainless Steel	1:	3 4ft	1.25	
Copper Cald Stainless Steel	13	.5 4ft	1.35	
Copper Cald Stainless Steel	14	4 4ft	1.45	Driving Stud &
Copper Cald Stainless Steel	12	2 6ft	1.6	Driving
Copper Cald Stainless Steel	10	B 6ft	1.88	Head Could be
Copper Cald Stainless Steel	13	.5 6ft	2.02	Galvanised Steel
Copper Cald Stainless Steel	14	4 6ft	2.18	or Stainless
Pure Copper Pipe & Stainless Steel	Core 13	3 4ft	1.35	Steel
Pure Copper Pipe & Stainless Steel	Core 13	B 6ft	1.98	
Pure Copper Pipe & Stainless Steel	Core 14	4 4ft	1.55	
Pure Copper Pipe & Stainless Steel	Core 14	4 6ft	2.28	

